

CABLE SPECIFICATIONS

Option - "Z"

DATA SHEET PART SERIES: Options

SHEET 1 OF 1

Revision
0816

Cable Option - "Z" Our "Weather-proof Sealing" Techniques ensure a water tight barrier between the connector back body and the cable jacket. **This option is standard with all available weatherized configurations** including Weatherized PVC (Option - W), Armorized Weatherized (Option- AW), Armorized Neoprene (Option- AN)
*Stand alone "Weather Proof Sealing" (Option-Z) does not include UV protection of the cable and is available for Lab-Flex® and Lab-Flex® S families including as a standard on Lab-Flex® 290 and Lab-Flex® 335 cable assemblies.

Typical Applications

- Harsh Chemical Environments
- Environmental Testing
- Production and Lab Testing
- Outdoor Testing

Option inclusion		
Available Options	Automatically Included?	Description
Option - "A" (Armorized)	No	
Option - "AW" (Armorized & Weatherized)	Yes	"Z" does not need to be called out in product code
Option - "MC" (Monocoil)	No	
Option - "MP" (Armorized Monocoil)	No	
Option - "W" (Weatherized)	Yes	"Z" does not need to be called out in product code
Option - "AN" (Armorized Neoprene)	Yes	"Z" does not need to be called out in product code

* NOTE:

Option - "Z" is also available for all Lab-Flex® & Lab-Flex® S that are not provided with the above options. To order Option - "Z", add Letter "Z" after the cable code in the ordering part number.

Example: **SMS-200Z-48.0-SMS**
SMS-200AZ-48.0-SMS Option - "Z" added after "A"
SMS-200W-48.0-SMS Option - "Z" already included (See above)
SMS-290/335-48.0-SMS Option - "Z" comes standard. (See above)