

TITLE: SPECIFICATION CONTROL DRAWING

PART IDENTIFIER: HR05XXX

(X)=TEST CODE: A=GROUP A; B=GROUP B; C=GROUP C
 (XX)=DB VALUE (01-20DB)

DESCRIPTION: CHIP ATTENUATOR WITH HIGH RELIABILITY TESTING.

NOTE: SINGLE LOT AND DATE CODE AVAILABLE UPON REQUEST.

ASSEMBLY DWG: N/A

1.0 SPECIFICATIONS:

- 1.1 ELECTRICAL:
 - 1.1.1 IMPEDANCE: 50 OHMS NOMINAL.
 - 1.1.2 FREQUENCY RANGE: DC-18 GHZ.
 - 1.1.3 ATTENUATION VALUES AVAILABLE: 0-20 DB IN 1 DB INCREMENTS.
 - 1.1.4 ATTENUATION ACCURACY: SEE TABLE.
 - 1.1.5 ATTENUATION STABILITY: 0.0001 DB/DB/C°

ATTENUATION ACCURACY				
DB	DC - 4 GHZ	4 - 8 GHZ	8 - 12.4 GHZ	12.4 - 18 GHZ
0	-0,+3	-0,+5	-0,+5	-0,+5
1 -3	±0.3	±0.5	±0.5	±0.5
4 - 6	±0.4	±0.5	±0.5	±0.75
7 - 10	±0.5	±0.5	±0.75	±1.0
11 - 15	±0.75	+0.5,-3.0	+0.5,-3.5	---
16 - 20	±1.0	+0.5,-4.0	+1.0,-6.0	---

- 1.1.6 VSWR: DC - 4 GHZ - 1.25 MAX 8 - 18 GHZ - 1.50 MAX
 4 - 8 GHZ - 1.35 MAX
- 1.1.7 INPUT POWER: 100 MILLIWATTS CW.
 - 1.1.7.1 FULL RATED POWER TO 125°C, DERATED LINEARLY TO 0 WATTS AT 150°C.
 - 1.1.7.2 PEAK POWER, 1 WATT FOR 10US PULSE WIDTH @ 1% DUTY CYCLE.

1.2 MECHANICAL:

- 1.2.1 OUTLINE DWG: SEE SHEET 3.
- 1.2.2 WORKMANSHIP: PER MIL-PRF-55342.

1.3 ENVIRONMENTAL:

- 1.3.1 ALTITUDE:
 - 1.3.1.1 NON-OPERATING: SEA LEVEL TO 50,000 FEET.
 - 1.3.1.2 OPERATING: SEA LEVEL TO 50,000 FEET.
- 1.3.2 TEMPERATURE RANGE:
 - 1.3.2.1 NON-OPERATING: -55° C TO +150° C.
 - 1.3.2.2 OPERATING: -55°C TO +150°C.
- 1.3.3 VIBRATION: PER MIL-STD-202, METHOD 204, COND. D.
- 1.3.4 SHOCK: PER MIL-STD-202, METHOD 213, COND. I.
- 1.3.5 MOISTURE RESISTANCE: PER MIL-STD-202, METHOD 106 EXCEPT SUBCYCLE STEPS 7A AND 7B AND POLARIZATION AND LOAD ARE NOT APPLICABLE.

2.0 UNIT MARKING: MARKED WITH COLOR DOT AND ORIENTATION LINE . LEGIBILITY AND PERMANENCY PER MIL-STD-130.


3.0 QUALITY ASSURANCE:

- 3.1 VERIFY 100% VISUAL PRE-CAP INSPECTION PERFORMED PER TP-8965.
- 3.2 PREFORM GROUP A, B AND/OR C TESTING AS INDICATED BY THE PART NUMBER PER TP-8965.
- 3.3 TEST DATA REQUIREMENTS:
 - 3.3.1 TEST DATA REQUIRED FOR CUSTOMER - SEE PARAGRAPH 5.0 OF TP-8965.
 - 3.3.2 DATA RETENTION - 24 MONTHS.
 - 3.3.3 TEST SAMPLES REQUIRED FOR CUSTOMER - SEE PARAGRAPH 5.0 OF TP-8965.

4.0 PACKAGING: STANDARD PACK PER 755W002. (SERIALIZED WAFFLE PACK)

EMC TECHNOLOGY 8851 SW OLD KANSAS AVE. STUART, FL 34997	CAGE CODE # 24602		DWG #	1009955000
	CHANGE NOTICE	EN 09-E1001	REV LVL	B
			SHEET	1 <u>OF</u> 3

PART ID REF
HR05XXX




MECHANICAL SPECIFICATIONS:

SUBSTRATE:
 MATERIAL - ALUMINA, MIL-I-10.
TERMINAL:
 MATERIAL - THICK FILM, NICKEL BARRIER, SOLDER PLATED.
RESISTIVE ELEMENT:
 MATERIAL - THIN FILM, TANTALUM NITRIDE.

REFERENCE TABLE					
dB VAL	DOT COLOR		dB VAL	DOT COLOR	
	1st	2nd		1st	2nd
0	BLK	---	11	BRN	BRN
1	BRN	---	12	BRN	RED
2	RED	---	13	BRN	ORG
3	ORG	---	14	BRN	YEL
4	YEL	---	15	BRN	GRN
5	GRN	---	16	BRN	BLU
6	BLU	---	17	BRN	VIO
7	VIO	---	18	BRN	GRY
8	GRY	---	19	BRN	WHT
9	WHT	---	20	RED	BLK
10	BRN	BLK			

METRIC EQUIVALENTS GIVEN IN [mm]
 FOR REFERENCE INFORMATION ONLY

POWER RATING AND DERATING



<p>8851 SW OLD KANSAS AVE STUART, FL 34997 PHONE NO. (772)286-9300 FAX NO. (772)283-5286</p>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES FRACT --- ANG --- XX --- XXX ±0.005 XXXX ---	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EMC TECHNOLOGY INC AND SHALL NOT BE DUPLICATED OR USED AS BASIS FOR THE MANUFACTURE OR SALE OF PARTS OR DEVICES WITHOUT PERMISSION.			
	CAGE CODE 24602	SCALE 32:1	DRAWN BY JG 12/8/04	CHECKED BY	APPROVED BY DAR 12/8/04
	REV B	CHANGE NOTICE EN 09-E1001	DRAWING NO 1009955000	SHEET 2 OF 2	