

		DRAWING NO.	12-0002	REV	D
REQUIREMENTS	RATING	REQUIREMENTS	RATING		
NOMINAL IMPEDANCE (OHMS)	50	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G's)		
FREQUENCY RANGE (GHZ)	DC-26.5	SHOCK	MIL-STD-202 METHOD 213 COND. I (100 G's)		
TEMPERATURE COEFFICIENT	200 PPM	THERMAL SHOCK	MIL-STD-202 METHOD 107 COND. B (-65 TO +125 °C)		
OPERATING TEMPERATURE (°C)	-55 TO +125	BAROMETRIC PRESSURE	MIL-STD-202 METHOD 105 COND. C		
VSWR (MAXIMUM)	1.10:1	INTERFACE DIMENSIONS	MIL-STD-348 SMA SERIES		
AVERAGE POWER (WATTS)	0.5	TORQUE REQUIREMENT	MIL-D-39030/3 SMA SERIES 7-10 IN/LBS (PER PAIR)		
DC RESISTANCE	50 OHMS ± 5%				
<p>AVERAGE POWER DERATING</p>					
TITLE TERMINATION, COAXIAL SMA		DRAWING NO.		REV	
		DRAWN BLP 07/08/98		12-0002	
P.O. BOX 899 STUART, FL. 34995		SHEET 2 OF 2		D	