



## ORDERING INFORMATION

**PART IDENTIFIER: CT2335AF**

## SPECIFICATIONS

### 1. ELECTRICAL:

Impedance:	50 $\Omega$ Nominal.
Frequency:	DC - 2 GHz.
VSWR:	1.30:1 Max.
Input Power:	Heat Sink 85°C: 90 Watts. (Derate Power Linearly To 0 Watts @ 125°C).

### 2. ENVIRONMENTAL:

Non-Operating Temperature:	-55°C To +150°C.
Operating Temperature:	-55°C To +125°C.

### 3. MARKING:

Unit Marking:	No Marking.
---------------	-------------

### 4. QUALITY ASSURANCE:

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL = 1.0.

Visual And Mechanical Per 824W154.

Data Requirements:

No Test Data Required for Customer.

Data Retention – 24 Months.

### 5. PACKAGING:



Standard Pack per 755W002.

### 6. MECHANICAL:

Substrate (Material):	Aluminum Nitride MIL-I-10.
Terminals and Ground Plane (Material):	Thick Film, Lead Free Plating, RoHS Compliant.
Resistive Element (Material):	Thick Film.



## POWER RATING AND DERATING



Unless Otherwise Specified:

TOLERANCE: X.XX =  $\pm 0.02$  X.XXX =  $\pm 0.010$ .