



RESISTOR CVD DIAMOND CHIP 2.25 WATTS, WRAPPED

DATASHEET PART SERIES: CR0505DX5W2

Sheet 1 of 2

ECO-082845

Doc# CR0505DX5W2-1013125


Revision A

ORDERING INFORMATION

Part Identifier:

CR0505DX5W2

Resistance



SPECIFICATIONS

1.0 ELECTRICAL

Resistance:	50 & 100 Ω , $\pm 5\%$
Frequency Range:	DC – 18 GHz
Capacitance:	0.30 pF Typical
Input Power CW:	2.25 Watts
Peak Power:	22.5 Watts (1 μ s pulse width/1% duty cycle)

2.0 ENVIRONMENTAL

Operating Temperature:	-55 °C To +125 °C
Temperature Coefficient:	± 200 PPM/°C Max

3.0 MARKING

Unit Marking:	None
---------------	------

4.0 QUALITY ASSURANCE

Sample Inspect Per MIL-STD-105, Level II, 1.0% AQL
 Visual and Mechanical Inspection for Conformance to Outline Drawing
 Measure DC Resistance
 Data Retention - Standard

5.0 PACKAGING

Standard:	Waffle Packaging
Optional:	Tape and Reel



RESISTOR CVD DIAMOND CHIP 2.25 WATTS, WRAPPED

DATASHEET PART SERIES: CR0505DX5W2

Sheet 2 of 2



ECO-082845

Doc# CR0505DX5W2-1013125

Revision A

6.0 MECHANICAL

Substrate Material:	CVD Diamond
Resistive Element:	Thin Film
Terminal/Material:	Gold over Nickel
Ground Plane Material:	Gold over Platinum
Metric Dimensions:	Provided for reference only

Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.01 X.XXX = ± 0.005