


# TS06 Series

ATTENUATOR CHIP DC-20GHZ



Smiths Interconnect is the world leader in chip attenuators offering the widest selection of products from DC through Q band. Chip components are offered on Alumina, Aluminum Nitride, Beryllium Oxide, and CVD Diamond for a wide range of applications. Backed by proven performance and significant heritage, Smiths Interconnect is the leader in high reliability components.

The TS06 platform offers best in class performance from DC-20 GHz in a small package size. Rated for DC-20 GHz with excellent broadband response, the TS06 series of products has a wide range of applications. It is constructed on an Alumina substrate with rugged thin film terminations and passivated Tantalum Nitride resistive elements. The product also includes a protective coating for added protection from various environmental conditions. Multiple attenuation values and surface finishes are available for RoHS and tin lead solder applications.

TS06 Series Chip Attenuators offers best in class performance from DC-20 GHz in a small package size.

## Features and Benefits

- Small Footprint
- Multiple Terminal Finishes
- Broad Frequency Range
- Low VSWR
- Wide Range of Attenuation Values
- Tight Attenuation Tolerance

## Applications

- Amplifier Circuits
- Transmit/Receive Modules
- Up/Down Converters
- Instrumentation
- Satellite Communications
- Radar
- Broadcast

# Technical Characteristics

Mounting Configuration Options	Planar
--------------------------------	--------

## Electrical

Nominal Impedance	50 ohms					
Frequency Range	DC -20 GHz					
Attenuation Values Available	0-12, 15 & 20 dB in 1 dB Increments					
Attenuation Accuracy	<b>ATTENUATION ACCURACY (dB)</b>					
	Attenuation Value (dB)	DC-10 GHz		10-20 GHz		
	0	Continuity Only				
	1-9	± 0.50		± 0.50		
	10-12, 15 & 20	± 0.75		± 1.00		
Input Power CW	<b>INPUT POWER (CW)</b>					
	dB	Watts	dB	Watts	dB	Watts
	0-1	3.0	2-3	1.0	10-12, 15 & 20	0.5
Peak Power	10X CW power based on 1 µS pulse width @ 1% Duty Cycle					
VSWR	DC-10GHz 1.25:1 Max, 10-20GHz 1.35:1 Max					

## Environmental

Operating Temperature	-55°C to +150°C
Storage Temperature	-65°C to +150°C
Temperature Coefficient	± 200 PPM/°C Max
Moisture Sensitivity Level	MSL 1 - Unlimited

## Mechanical

Substrate Material	Alumina (Al <sub>2</sub> O <sub>3</sub> ) 96%
Resistive Film	Thin Film, Tantalum Nitride
Protective Coating	Silicon Nitride
Finish Options	Blank
	-F Solder Plated (Sn60/Pb40)
	-F Solderable Gold over Nickel (RoHS Compliant)
	-S Pretinned (Sn60/Pb40)

## Marking

Unit Marking	Orientation dot and dB Value
--------------	------------------------------


## Quality Assurance

	Sample visual and mechanical inspection - 1.0 AQL per mechanical drawing requirements. Periodic electrical inspection performed for commercial grade products. High reliability tested products are available per MIL-PRF-55342.
--	--

## Packaging


Standard Packaging	Tape and Reel or Waffle Pack
--------------------	------------------------------

# Power Derating Curve




# Typical Data

## TS06XX Series Attenuation



# Mechanical


## TS06XX Series Attenuation



Unless otherwise specified, tolerance: X.XXX = ±0.005"

# Suggested Mounting Footprint

Part Number	Inches						Millimeters					
	A	B	C	D	S	W	A	B	C	D	S	W
TS06xxF	0.018	0.018	0.033	0.020	0.016	0.068	0.46	0.46	0.84	0.51	0.41	1.73



## How To Order

Specify Model Number: **TS06XXX**

	<b>T S 0 6</b>				
	<b>1</b>		<b>2</b>		<b>3</b>
<b>1 Series Name</b>	<b>T S 0 6</b> Series				
<b>2 Attenuation Value</b>	<b>0 0</b> 00 dB through 12.0 dB	<b>1 5</b> 15.0 dB	<b>2 0</b> 20.0 dB		
<b>3 Terminal Finish</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> <b>S</b> Pretinning	<input type="checkbox"/> <b>F</b> RoHS		

# Worldwide Support

## Connectors

### Americas

#### Sales

connectors.uscsr@smithsinterconnect.com

#### Technical Support

connectors.ustechsupport@smithsinterconnect.com

### Europe

#### Sales

connectors.emeacsr@smithsinterconnect.com

#### Technical Support

connectors.emeatechsupport@smithsinterconnect.com

### Asia

#### Sales

asiacsr@smithsinterconnect.com

#### Technical Support

asiatechsupport@smithsinterconnect.com

## Fibre Optics & RF Components

### Americas

#### Sales

focom.uscsr@smithsinterconnect.com

#### Technical Support

focom.techsupport@smithsinterconnect.com

### Europe

#### Sales

focom.emeacsr@smithsinterconnect.com

#### Technical Support

focom.techsupport@smithsinterconnect.com

### Asia

#### Sales

focom.asiacsr@smithsinterconnect.com

#### Technical Support

focom.techsupport@smithsinterconnect.com

## Semiconductor Test

### Americas

#### Sales

semi.uscsr@smithsinterconnect.com

#### Technical Support

semi.techsupport@smithsinterconnect.com

### Europe

#### Sales

semi.emeacsr@smithsinterconnect.com

#### Technical Support

semi.techsupport@smithsinterconnect.com

### Asia

#### Sales

semi.asiacsr@smithsinterconnect.com

#### Technical Support

semi.techsupport@smithsinterconnect.com

## RF/MW Subsystems

### Americas, Europe & Asia

#### Sales

subsystems.csr@smithsinterconnect.com

#### Technical Support

subsystems.techsupport@smithsinterconnect.com

## Connecting Global Markets

more > [smithsinterconnect.com](https://www.smithsinterconnect.com) | [in](#) [twitter](#) [youtube](#)