

ATTENUATOR TEMPERATURE VARIABLE



DATA SHEET

PART SERIES: TVAXX00X0XWB1

SHEET 1 OF 2
Dwg 1004005

EN 16-0736
Revision D

FEATURES

- Temperature Variable
- Compact Package
- Wideband Performance
- Passive Gain Compensation
- Rugged Construction
- MIL-PRF-3933

APPLICATIONS

- Power Amplifiers
- Instrumentation
- Mobile Networks
- Point-to-Point Radios
- Satellite Communications
- Military Radios
- Up/Down Converters




GENERAL DESCRIPTION

EMC Technology is the leading authority in temperature variable attenuators. Thermopad[®] temperature variable attenuators have been a highly reliable passive solution for over temperature gain compensation for more than 20 years. All Thermopad[®] products can be qualified for high-reliability and space applications.

ORDERING INFORMATION

Part Identifier: TVAXX00X0XWB1



SPECIFICATIONS

1.0 ELECTRICAL

Nominal Impedance:	50 ohms
Frequency Range:	DC-6.0 GHz
Attenuation Values Available:	1-10dB in 1dB increments
Attenuation Accuracy:	@ 25°C: ± 0.5 dB @ 1GHz
VSWR:	1.30:1 Max. @ 1GHz
Input Power	Negative Shifting: 2 Watts cw. Positive Shifting: 0.25 Watts cw. Full Rated Power to 125°C, Derated Linearly to 0 Watts @ 150°C.
Temperature Coefficient of Attenuation:	-0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C
Temperature Coefficient Tolerance:	± 0.001 dB/dB/°C

2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C
Non-operating Temperature:	-65°C to +150°C

3.0 MARKING

Unit Marking:	None
---------------	------

4.0 QUALITY ASSURANCE

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL=1.0.
Visual and Mechanical Examination for Conformance to Outline Drawing Requirements
Sample Inspection (Destructive Testing).

Select three (3) units from lot and measure DCA every 20°C over the temperature range of

ATTENUATOR TEMPERATURE VARIABLE



DATA SHEET

PART SERIES: TVAXX00X0XWB1

SHEET 2 OF 2
Dwg 1004005

EN 16-0736
Revision D

-55°C to +125°C; Calculate using linear regression, the slope of the curve.

Calculate TCA using the following formula:

$$TCA = \frac{\text{Slope}}{\text{Attenuation @ 25°C}}$$

Inspection in accordance with 824W107

Test Data Requirements:

No Data Required for Customer

Data Retention – 24 Months


5.0 PACKAGING

Standard:

Tape and Reel

6.0 MECHANICAL

Substrate Material: Alumina, 96% MIL-I-10
Terminal Material: Thick Film Barrier, Bondable Gold
Workmanship: Per MIL-PRF-55342
Ground Plane: Thick Film
Resistive Element: Thick Film
Metric Dimensions: Provided for reference only



Unless Otherwise Specified: X.XXX = ± 0.005