



K Series

Medium & High Density PCB Connectors



Hypertac® Hyperboloid Technology

Smiths Interconnect, a Molex company, offers an extensive range of superior contact technologies suitable for standard and custom solutions. Hypertac® (HYPERboloid conTACT) is the original superior performing hyperboloid contact technology designed for use in all applications and in harsh and demanding environments where high reliability and safety are critical. The inherent electrical and mechanical characteristics of the Hypertac hyperboloid contact ensures unrivalled performance in terms of reliability, number of mating cycles, low contact force and minimal contact resistance. The shape of the contact sleeve is formed by hyperbolically arranged contact wires, which align themselves elastically as contact lines around the pin, providing a number of linear contact paths.



Features

Benefits

Low insertion/extraction forces

The angle of the socket wires allows tight control of the pin insertion and extraction forces. The spring wires are smoothly deflected to make line contact with the pin.

High density interconnect systems

Significant reductions in size and weight of sub-system designs. No additional hardware is required to overcome mating and unmating forces.

Long contact life

The smooth and light wiping action minimizes wear on the contact surfaces. Contacts perform up to 100,000 insertion/extraction cycles with minimal degradation in performance.

Low cost of ownership

The Hypertac contact technology will surpass most product requirements, thus eliminating the burden and cost of having to replace the connector or the entire subsystem.

Lower contact resistance

The design provides a far greater contact area and the wiping action of the wires insures a clean and polished contact surface. Our contact technology has about half the resistance of conventional contact designs.

Low power consumption

The lower contact resistance of our technology results in a lower voltage drop across the connector reducing the power consumption and heat generation within the system.

Higher current ratings

The design parameters of the contact (e.g., the number, diameter and angle of the wires) may be modified for any requirement. The number of wires can be increased so the contact area is distributed over a larger surface. Thus, the high current carried by each wire because of its intimate line contact, can be multiplied many times.

Maximum contact performance

The lower contact resistance of the Hypertac contact reduces heat build-up; therefore Hypertac contacts are able to handle far greater current in smaller contact assemblies without the detrimental effects of high temperature.

Immunity to shock & vibration

The low mass and resultant low inertia of the wires enable them to follow the most abrupt or extreme excursions of the pin without loss of contact. The contact area extends 360° around the pin and is uniform over its entire length. The 3 dimensional symmetry of the Hypertac contact design guarantees electrical continuity in all circumstances.

Reliability under harsh environments

Harsh environmental conditions require connectors that will sustain their electrical integrity even under the most demanding conditions such as shock and vibration. The Hypertac contact provides unmatched stability in demanding environments when failure is not an option.

Contents

KN Series - Medium Density PCB Connectors

KNB series (2 rows).....	2
KXB series (2 rows).....	18
KNC/KND series (3 rows)	21
Contacts	36
Tools and accessories.....	37

KM Series - High Density PCB Connectors

KMC Series (3 rows)	40
KMH Series (3 rows)	62
Power & High Frequency Contacts	66
Tools and accessories.....	67

Technical Characteristics

Contact diameter	HYPERTAC® type Ø 0.60 mm rear removable
Number of contact	Up to 120
Pitch	2.54 mm between rows - 1.27 mm between quicuncial contacts
Rows	2

Materials & Platings

Contact	Brass or bronze	
Moulding	Glass fiber filled diallyl - Phtalate	
Guides	Stainless steel or nickel plated brass	
	Standard	ESA
Pin body	0.25 µm gold / 1.27 µm Ni	1.27 µm gold / 1.27 µm Ni (min.)
Socket body	0.25 µm gold / 1.27 µm Ni on active area 1.27 µm Ni on non active area	0.25 µm gold / 1.27 µm Ni (min.)
Socket wires	1 µm gold / 0.20 µm Ni	1.27 µm gold / 0.20 µm Ni (min.)

Electrical

Current grade rating (at 25°C)	Standard grade: 3 A max. - ESA grade: 5 A max.
Dielectric withstanding voltage	1200 Vrms
Contact resistance	≤8 mΩ
Insulation resistance	>104 MΩ (500 Vcc)

Mechanical

Mating & unmating cycle	5000
Guiding	By two outside guides (2 guiding styles) and one central guide (3 guiding styles)
Keying	By rotating of outside polarised guides (up to 36 keying)

Environmental

Temperature range	-55°C to 125°C
Conformity	MIL C 55302, ESA/ESCC3401/016 - 3401/017, NF C-UTE C 93-424

How To Order



K

N

B

1234567

1	Series	
2	Pitch or type	N 1.27 mm pitch, rear removable contacts
3	Model	B 2 rows
4	Number of contacts	017 029 041 053 065 072 084 096 120 For the right angle 053 layout, KNB must be replaced by KXB (non ESA qualified, details on page 20)
5	Moulding polarity	NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE 12145454 Female plug 13155555 Male plug 16185656 Tinned female plug[†] 17195757 Tinned male plug[†] NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE 1A1C5A5A Tinned female plug^{**†} 1B1D5B5B Tinned male plug^{**†} 22244444 Female receptacle 23254545 Male receptacle NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE 26284646 Tinned female receptacle[†] 27294747 Tinned male receptacle[†] 2A2C-- Tinned female receptacle^{**†} 2B2D-- Tinned male receptacle^{**†}
6	Termination styles	10 Through board solder - 90°- length 3 mm 11 Through board solder - 90°- length 4 mm 12 Through board solder - 90°- length 4.50 to 5.70 mm 20 Crimp 21 Double Crimp 30 Through board solder - straight 31 Through board solder - straight 40 Solder bucket 51 Wire wrap (3 wrapping levels) 90 Male - male 91 Female - male
7	Mounting hardware	Guide Style (consult us for special guides) 110 Male polarised, transverse mount, standard plug 111 Male polarised, vertical mount 113 Male polarised, float mount 121 Female polarised, vertical mount 123 Female polarised, float mount 124 Female polarised, transverse mount 145 Male polarised, transverse mount on receptacle only 190 Female power or mass contact, vertical mount 125 Male unpolarised, transverse mount 126 Female unpolarised, vertical mount 127 Male unpolarised, vertical mount 130 Female unpolarised, vertical mount 131 Male unpolarised, transverse mount 132 Female unpolarised, transverse mount 133 Female all polarised, transverse mount 191 Male power or mass contact, vertical mount Locking Styles MALE PLUG 201 1/4 turn, free connector 203 1/4 turn, transverse mount 207 Jackscrew, free connector 211 Jackscrew, free connector 290 Jackscrew, vertical mount FEMALE RECEPTACLE 202 1/4 turn, vertical mount 204 1/4 turn, transverse mount 208 Jackscrew, transverse mount 210 Jackscrew, free connector 212 Jackscrew, transverse mount 215 Jackscrew, vertical mount 219 Jackscrew, vertical mount 232 Jackscrew, with operation button

*

For 90° & straight terminations (splicing on PCB)

**

RoHS compliant for 90° & straight terminations (splicing on PCB)

†

Tinned contacts are not available as spares

Hypertac & ESA Correspondance Table

HYPERTAC

KNB

34 01 016 01 B

1

2

3

4

5

6

1 ESCC component number																																																																																																																								
2 Mounting	HYPERTAC ESA <table><tr><td>Plug KNB 017</td><td>01</td><td>Plug KNB 096</td><td>08</td><td>Receptacle KNB 053</td><td>16</td><td>Plug KNB 072</td><td>56</td><td>Plug KNC 098</td><td>62</td></tr><tr><td>Plug KNB 029</td><td>02</td><td>Plug KNB 120</td><td>10</td><td>Receptacle KNB 065</td><td>17</td><td>Receptacle KNB 072</td><td>57</td><td>Receptacle KNC 098</td><td>63</td></tr><tr><td>Plug KNB 041</td><td>03</td><td>Plug KNC 160</td><td>12</td><td>Receptacle KNB 084</td><td>19</td><td>Plug KNC 062</td><td>58</td><td></td><td></td></tr><tr><td>Plug KNB 053</td><td>04</td><td>Receptacle KNB 017</td><td>13</td><td>Receptacle KNB 096</td><td>20</td><td>Receptacle KNC 062</td><td>59</td><td></td><td></td></tr><tr><td>Plug KNB 065</td><td>05</td><td>Receptacle KNB 029</td><td>14</td><td>Receptacle KNB 120</td><td>22</td><td>Plug KNC 080</td><td>60</td><td></td><td></td></tr><tr><td>Plug KNB 084</td><td>07</td><td>Receptacle KNB 041</td><td>15</td><td>Receptacle KNC 160</td><td>24</td><td>Receptacle KNC 080</td><td>61</td><td></td><td></td></tr></table> REMINDER SPATIAL P.P.P. (Party Polarity Protection) <table><tr><td>Female receptacle</td><td>44</td><td>Plug female</td><td>54</td></tr><tr><td>Male receptacle</td><td>45</td><td>Plug male</td><td>55</td></tr></table> EXAMPLE KNB 029 44 40 113 P.P.P.	Plug KNB 017	01	Plug KNB 096	08	Receptacle KNB 053	16	Plug KNB 072	56	Plug KNC 098	62	Plug KNB 029	02	Plug KNB 120	10	Receptacle KNB 065	17	Receptacle KNB 072	57	Receptacle KNC 098	63	Plug KNB 041	03	Plug KNC 160	12	Receptacle KNB 084	19	Plug KNC 062	58			Plug KNB 053	04	Receptacle KNB 017	13	Receptacle KNB 096	20	Receptacle KNC 062	59			Plug KNB 065	05	Receptacle KNB 029	14	Receptacle KNB 120	22	Plug KNC 080	60			Plug KNB 084	07	Receptacle KNB 041	15	Receptacle KNC 160	24	Receptacle KNC 080	61			Female receptacle	44	Plug female	54	Male receptacle	45	Plug male	55																																																			
Plug KNB 017	01	Plug KNB 096	08	Receptacle KNB 053	16	Plug KNB 072	56	Plug KNC 098	62																																																																																																															
Plug KNB 029	02	Plug KNB 120	10	Receptacle KNB 065	17	Receptacle KNB 072	57	Receptacle KNC 098	63																																																																																																															
Plug KNB 041	03	Plug KNC 160	12	Receptacle KNB 084	19	Plug KNC 062	58																																																																																																																	
Plug KNB 053	04	Receptacle KNB 017	13	Receptacle KNB 096	20	Receptacle KNC 062	59																																																																																																																	
Plug KNB 065	05	Receptacle KNB 029	14	Receptacle KNB 120	22	Plug KNC 080	60																																																																																																																	
Plug KNB 084	07	Receptacle KNB 041	15	Receptacle KNC 160	24	Receptacle KNC 080	61																																																																																																																	
Female receptacle	44	Plug female	54																																																																																																																					
Male receptacle	45	Plug male	55																																																																																																																					
3 Termination style	HYPERTAC ESA <table><tr><td>Bent male 10</td><td>MC</td><td>Solder bucket male 40</td><td>MS</td><td>Bent female tinned 10</td><td>FA</td><td>Mini-wrapping female 51</td><td>FY</td></tr><tr><td>Bent male tinned 10</td><td>MA</td><td>Mini-wrapping male 51</td><td>MY</td><td>Crimp female 20</td><td>FR</td><td>Bent long female 11</td><td>FL</td></tr><tr><td>Crimp male 20</td><td>MR</td><td>Bent long male 11</td><td>ML</td><td>Straight female 30</td><td>FD</td><td>Bent long female tinned 11</td><td>FG</td></tr><tr><td>Straight male 30</td><td>MD</td><td>Bent long male tinned 11</td><td>MG</td><td>Straight female tinned 30</td><td>FE</td><td>Female-male 91</td><td>FM</td></tr><tr><td>Straight male tinned 30</td><td>ME</td><td>Bent female 10</td><td>FC</td><td>Solder bucket female 40</td><td>FS</td><td></td><td></td></tr></table>	Bent male 10	MC	Solder bucket male 40	MS	Bent female tinned 10	FA	Mini-wrapping female 51	FY	Bent male tinned 10	MA	Mini-wrapping male 51	MY	Crimp female 20	FR	Bent long female 11	FL	Crimp male 20	MR	Bent long male 11	ML	Straight female 30	FD	Bent long female tinned 11	FG	Straight male 30	MD	Bent long male tinned 11	MG	Straight female tinned 30	FE	Female-male 91	FM	Straight male tinned 30	ME	Bent female 10	FC	Solder bucket female 40	FS																																																																																	
Bent male 10	MC	Solder bucket male 40	MS	Bent female tinned 10	FA	Mini-wrapping female 51	FY																																																																																																																	
Bent male tinned 10	MA	Mini-wrapping male 51	MY	Crimp female 20	FR	Bent long female 11	FL																																																																																																																	
Crimp male 20	MR	Bent long male 11	ML	Straight female 30	FD	Bent long female tinned 11	FG																																																																																																																	
Straight male 30	MD	Bent long male tinned 11	MG	Straight female tinned 30	FE	Female-male 91	FM																																																																																																																	
Straight male tinned 30	ME	Bent female 10	FC	Solder bucket female 40	FS																																																																																																																			
4 Locking type On left side	HYPERTAC ESA <table><tr><td>Guideless connector</td><td>00</td><td>KNB</td><td>145</td><td>40</td><td>KNC</td><td>10</td><td>209</td><td>49</td><td>KNB</td><td>11</td><td>125</td><td>71</td><td>KNB</td><td>11</td><td>208</td><td>79</td></tr><tr><td>KNB</td><td>131</td><td>31</td><td>KNB</td><td>124</td><td>41</td><td>KN</td><td>210</td><td>50</td><td>KNB</td><td>11</td><td>110</td><td>72</td><td>KN</td><td>219</td><td>80</td><td></td></tr><tr><td>KNB</td><td>132</td><td>32</td><td>KNC</td><td>10</td><td>230</td><td>43</td><td>KN</td><td>211</td><td>51</td><td>KNB</td><td>10</td><td>230</td><td>73</td><td>KN</td><td>290*</td><td>81</td></tr><tr><td>KNB</td><td>10</td><td>110</td><td>33</td><td>KN</td><td>232</td><td>45</td><td>KNB</td><td>212</td><td>52</td><td>KNC</td><td>124</td><td>74</td><td></td><td></td><td></td><td></td></tr><tr><td>KNC</td><td>10</td><td>110</td><td>34</td><td>KN</td><td>231</td><td>46</td><td>KN</td><td>215</td><td>53</td><td>KNC</td><td>132</td><td>75</td><td></td><td></td><td></td><td></td></tr><tr><td>KN</td><td>111</td><td>35</td><td>KN</td><td>207</td><td>47</td><td>KN</td><td>123</td><td>54</td><td>KNC</td><td>11</td><td>110</td><td>76</td><td></td><td></td><td></td><td></td></tr><tr><td>KN</td><td>121</td><td>36</td><td>KNB</td><td>10</td><td>208</td><td>48</td><td>KN</td><td>113</td><td>55</td><td>KNC</td><td>11</td><td>125</td><td>77</td><td></td><td></td><td></td></tr></table>	Guideless connector	00	KNB	145	40	KNC	10	209	49	KNB	11	125	71	KNB	11	208	79	KNB	131	31	KNB	124	41	KN	210	50	KNB	11	110	72	KN	219	80		KNB	132	32	KNC	10	230	43	KN	211	51	KNB	10	230	73	KN	290*	81	KNB	10	110	33	KN	232	45	KNB	212	52	KNC	124	74					KNC	10	110	34	KN	231	46	KN	215	53	KNC	132	75					KN	111	35	KN	207	47	KN	123	54	KNC	11	110	76					KN	121	36	KNB	10	208	48	KN	113	55	KNC	11	125	77			
Guideless connector	00	KNB	145	40	KNC	10	209	49	KNB	11	125	71	KNB	11	208	79																																																																																																								
KNB	131	31	KNB	124	41	KN	210	50	KNB	11	110	72	KN	219	80																																																																																																									
KNB	132	32	KNC	10	230	43	KN	211	51	KNB	10	230	73	KN	290*	81																																																																																																								
KNB	10	110	33	KN	232	45	KNB	212	52	KNC	124	74																																																																																																												
KNC	10	110	34	KN	231	46	KN	215	53	KNC	132	75																																																																																																												
KN	111	35	KN	207	47	KN	123	54	KNC	11	110	76																																																																																																												
KN	121	36	KNB	10	208	48	KN	113	55	KNC	11	125	77																																																																																																											
5 Locking type In center	00 For 2 guide connectors -- For 3 guide connectors (see table 4, Locking type - On left side) HYPERTAC ESA <table><tr><td>KNB</td><td>10</td><td>125</td><td>26</td><td>KNC</td><td>10</td><td>125</td><td>27</td><td>KN</td><td>127</td><td>28</td><td>KN</td><td>126</td><td>29</td></tr></table>	KNB	10	125	26	KNC	10	125	27	KN	127	28	KN	126	29																																																																																																									
KNB	10	125	26	KNC	10	125	27	KN	127	28	KN	126	29																																																																																																											
6 Locking type On right side	(see table 4, Locking type - On left side)																																																																																																																							

* Please consult us

Contact Terminations

Plug

Male

Female

90° Through board solder

Ref: **10** (X=3)

Ref **Ⓒ**: **MC & FC / MA & FA** - Ref: **11** (X=4)





Ref **Ⓒ**: **ML & FL / MG & FG**

Ref: **12** (X= 4.50 mm min to 5.70 mm max)

Receptacle

Female





Male



Crimp (AWG 28-26 & 24-22)





Ref: **20**

Ref **Ⓒ**: **MR & FR**



Crimp (AWG 28-26 & 24-22) & Crimp on sheath (Ø 1.45)

Ref: **21**







Straight through board solder

Ref: **30**

Ref **Ⓒ**: **MD & FD / ME & FE**

Ref **31**

See: 90° Through board solder



Contact Terminations





Plug

Male

Female





Solder bucket (AWG 22 max)

Ref: **40** Ref : **MS & FS**





Wire wrap (3 wrapping levels)

Ref: **51** Ref : **MY & FY**





Saver (male-male)

Ref: **90**



Saver (female-male)


Ref: **91** Ref : **FM**




Connector Dimensions

Plug



17 to 65 contacts



Receptacle



72 to 120 contacts



No. of contacts	17	29	41	53	65	72	84	96	120
A	30.48	45.72	60.96	76.20	91.44	106.68	121.92	137.16	167.64
B max	38.50	53.70	69.00	84.20	99.50	114.70	129.90	145.20	175.50
C	20.32	35.56	50.80	66.04	81.28	-	-	-	-
D	-	-	-	-	-	43.18	50.80	58.42	73.66

Guide Device and Polarity Termination Compatibility Chart

Legend

	Compatible
	Compatible special saver connector

FP = Female Plug

FR = Female Receptacle

MR = Male Receptacle

MR 23	FR 22	FP 12	MP 13	MR 23	FR 22	FP 12	MP 13	MR 23	FR 22	FP 12	MP 13	MR 23	FR 22	FP 12	MP 13	MR 23	FR 22	FP 12	MP 13	Polarity				
																				Receptacle				Moulding
																				Plug				
																				90°	10	11	12	Contact
																				Straight		30	31	
																				Solder bucket			40	
																				Crimp		20	21	
																				Wire wrap			51	

[illegible]


Guide Styles

Plug & Receptacle

Male

Polarised vertical mount


Ref: 111 Ref : 35



Female


Polarised vertical mount

Ref: 121 Ref : 36




Polarised vertical float mount

Ref: 113 Ref : 55




Polarised vertical float mount

Ref: 123 Ref : 54




Unpolarised vertical mount

Ref: 127 Ref : 28




Polarised transverse mount

Ref: 124 Ref : 41




Unpolarised transverse mount

Ref: 131 Ref : 31



Unpolarised vertical mount

Ref: 126 Ref : 29




Guide Styles

Plug & Receptacle

Male

Polarised transverse mount


Ref: **145** Ref: : 40



Female


All polarised vertical mount

Ref: **130**




Unpolarised transverse mount

Ref: **132** Ref: : 32



All polarised transverse mount

Ref: **133**




Guide Styles

Plug & Receptacle

Male

Power or mass transverse mount


Ref: **191**



Female

Power or mass vertical mount


Ref: **190**



Plug Only


Polarised transverse mount

- Ref: **10 110** Ref: **33** **X=1.60 Y=3.20**
Ref: **11 110** Ref: **72** **X=2.40 Y=4.90**
Ref: **12 110** **X=3.20 Y=6.90**






Unpolarised transverse mount

- Ref: **10 125** Ref: **26** **X=1.60 Y=3.20**
Ref: **11 125** Ref: **71** **X=2.40 Y=4.90**
Ref: **12 125** **X=3.20 Y=6.90**



Locking Device Compatibility Chart


		R P		R P		R P		R P		R P		R P		R P			
Compatible																Receptacle	Moulding
																Plug	
P																	290
R																	
P																	231
R																	
P																	211
R																	
P																	207
R																	
P																	205
R																	
P																	203
R																	
P																	201
R																	
		Receptacle	Plug													Male locking devices	
		Moulding														Female locking devices	
																	
				232	219	215	212	210	208	204	202						

Male Locking Styles

Plug & Receptacle


Jack 1/4 turn lock, free connector

Ref: **201**




Jackscrew, free connector

Ref: **211** Ref: **51**




Jack 1/4 turn lock, transverse mount

Ref: **203** PCB thickness **1.60**




Jackscrew, vertical mount

Ref: **231** Ref: **46**




Jackscrew, free connector

Ref: **207** Ref: **47**



Jackscrew, vertical mount


Ref: **290** Ref: **81**




Female Locking Styles

Plug & Receptacle


Jack 1/4 turn lock, vertical mount

Ref: **202**


Jackscrew, transverse mount

Ref: **212** Ref: **52**

Jack 1/4 turn lock, transverse mount


Ref: **204**

Jackscrew, vertical mount


Ref: **215** Ref: **53**

Jackscrew, transverse mount


Ref: **10 208** Ref: **48** PCB thickness 1.60
 Ref: **11 208** Ref: **79** PCB thickness 2.40




Jackscrew, vertical mount

Ref: **219** Ref: **80**

Jackscrew, free connector

Ref: **210** Ref: **50**

Rotating jackscrew, free connector


Ref: **232** Ref: **45**

Mating Side Layout View


Plug




017



029




041




053




065




072



084











096




120

Receptacle




Panel Preparation Details

17 to 65 Contacts



72 to 120 Contacts



Panel: female or male, plug or receptacle, terminations 20 - 40 - 51

Guide styles: 111 - 121 - 126 - 127 - 130 - 190 (Fixed Mount) - 113 - 123 (Float Mount)


Locking styles: 202 - 215* - 219 - 231

*: for ref: 215, holes Ø 3.20 mm

No. of contacts	17	29	41	53	65	72	84	96	120
A	30.48	45.72	60.96	76.20	91.44	106.68	121.92	137.16	167.64
D	25.90	41.10	56.40	71.60	86.90	48.50	56.00	63.30	78.80

Mother board


72 to 120 Contacts



*: for ref: 215, holes Ø 3.20 mm

Daughter board

72 to 120 Contacts



(2) **Guide styles:** 110 - 125 - 191 **Locking styles:** 203 - 208

17

Technical Characteristics

Contact diameter	HYPERTAC® type Ø 0.60 mm rear removable
Number of contact	53
Pitch	2.54 mm between rows - 1.27 mm between quincuncial contacts
Rows	2

Materials & Platings

Contact	Brass or bronze
Moulding	Glass fiber filled diallyl - Phtalate
Guides	Stainless steel or nickel plated brass
Pin body	0.25 µm gold / 1.27 µm Ni
Socket body	0.25 µm gold / 1.27 µm Ni on active area; 1.27 µm Ni on non active area
Socket wires	1 µm gold / 0.20 µm Ni

Electrical

Current rating (at 25°C)	3 A max.
Dielectric withstanding voltage	1200 Vrms
Contact resistance	≤8 mΩ
Insulation resistance	>104 MΩ (500 Vcc)

Mechanical

Mating & unmating cycle	5000
Guiding	By two outside guides (2 guiding styles) and one central guide (3 guiding styles)
Keying	By rotating of outside polarised guides (up to 36 keying)

Environmental

Temperature range	-55°C to 125°C
Conformity	NF C-UTE C 93-424

How To Order




1	Thermoplastic material	X																																																									
2	Moulding polarity	<table><tr><td colspan="3">NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE</td><td colspan="3">NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE</td><td colspan="3">NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE</td></tr><tr><td>12</td><td>14</td><td>54</td><td>Female plug</td><td>1A</td><td>1C</td><td>5A</td><td>Tinned female plug**</td><td>26</td><td>28</td><td>46</td><td>Tinned female receptacle*</td></tr><tr><td>13</td><td>15</td><td>55</td><td>Male plug</td><td>1B</td><td>1D</td><td>5B</td><td>Tinned male plug**</td><td>27</td><td>29</td><td>47</td><td>Tinned male receptacle*</td></tr><tr><td>16</td><td>18</td><td>56</td><td>Tinned female plug*</td><td>22</td><td>24</td><td>44</td><td>Female receptacle</td><td>2A</td><td>2C</td><td>-</td><td>Tinned female receptacle**</td></tr><tr><td>17</td><td>19</td><td>57</td><td>Tinned male plug*</td><td>23</td><td>25</td><td>45</td><td>Male receptacle</td><td>2B</td><td>2D</td><td>-</td><td>Tinned male receptacle**</td></tr></table>	NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE			NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE			NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE			12	14	54	Female plug	1A	1C	5A	Tinned female plug**	26	28	46	Tinned female receptacle*	13	15	55	Male plug	1B	1D	5B	Tinned male plug**	27	29	47	Tinned male receptacle*	16	18	56	Tinned female plug*	22	24	44	Female receptacle	2A	2C	-	Tinned female receptacle**	17	19	57	Tinned male plug*	23	25	45	Male receptacle	2B	2D	-	Tinned male receptacle**
NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE			NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE			NF C-UTE C 93-424 MIL-C-55302 SPACE GRADE																																																					
12	14	54	Female plug	1A	1C	5A	Tinned female plug**	26	28	46	Tinned female receptacle*																																																
13	15	55	Male plug	1B	1D	5B	Tinned male plug**	27	29	47	Tinned male receptacle*																																																
16	18	56	Tinned female plug*	22	24	44	Female receptacle	2A	2C	-	Tinned female receptacle**																																																
17	19	57	Tinned male plug*	23	25	45	Male receptacle	2B	2D	-	Tinned male receptacle**																																																
3	Termination styles	<table><tr><td>10</td><td>Through board solder - 90° - length 3 mm</td><td>13</td><td>Through board solder - 90° - length 2.3 mm, plug only</td></tr><tr><td>11</td><td>Through board solder - 90° - length 4 mm</td><td>14</td><td>Through board solder - 90° - length 8 mm, receptacle only</td></tr><tr><td>12</td><td colspan="3">Through board solder - 90° - length 5.1 mm, plug only</td></tr></table>	10	Through board solder - 90° - length 3 mm	13	Through board solder - 90° - length 2.3 mm, plug only	11	Through board solder - 90° - length 4 mm	14	Through board solder - 90° - length 8 mm, receptacle only	12	Through board solder - 90° - length 5.1 mm, plug only																																															
10	Through board solder - 90° - length 3 mm	13	Through board solder - 90° - length 2.3 mm, plug only																																																								
11	Through board solder - 90° - length 4 mm	14	Through board solder - 90° - length 8 mm, receptacle only																																																								
12	Through board solder - 90° - length 5.1 mm, plug only																																																										
4	Mounting hardware	Guide Style*** <table><tr><td>110</td><td>Male polarised, transverse mount, standard plug</td><td>131</td><td>Male unpolarised, transverse mount</td></tr><tr><td>121</td><td>Female polarised, vertical mount</td><td>145</td><td>Male polarised, transverse mount on receptacle only</td></tr><tr><td>124</td><td>Female polarised, transverse mount</td><td>191</td><td>Male power or mass contact, vertical mount</td></tr><tr><td>125</td><td colspan="3">Male unpolarised, transverse mount</td></tr></table> Locking Styles*** <table><tr><td colspan="2">FEMALE RECEPTACLE</td><td colspan="2">MALE PLUG</td></tr><tr><td>204</td><td>1/4 turn, transverse mount</td><td>218</td><td>Jackscrew, transverse mount</td></tr><tr><td></td><td></td><td>203</td><td>1/4 turn, transverse mount</td></tr></table>	110	Male polarised, transverse mount, standard plug	131	Male unpolarised, transverse mount	121	Female polarised, vertical mount	145	Male polarised, transverse mount on receptacle only	124	Female polarised, transverse mount	191	Male power or mass contact, vertical mount	125	Male unpolarised, transverse mount			FEMALE RECEPTACLE		MALE PLUG		204	1/4 turn, transverse mount	218	Jackscrew, transverse mount			203	1/4 turn, transverse mount																													
110	Male polarised, transverse mount, standard plug	131	Male unpolarised, transverse mount																																																								
121	Female polarised, vertical mount	145	Male polarised, transverse mount on receptacle only																																																								
124	Female polarised, transverse mount	191	Male power or mass contact, vertical mount																																																								
125	Male unpolarised, transverse mount																																																										
FEMALE RECEPTACLE		MALE PLUG																																																									
204	1/4 turn, transverse mount	218	Jackscrew, transverse mount																																																								
		203	1/4 turn, transverse mount																																																								


* No RoHS compliant = 16 et 17
** RoHS Compliant = 1A et 1B

Connector Dimensions

Plug



Receptacle



Technical Characteristics

Contact diameter	HYPERTAC® type Ø 0.60 mm rear removable
Number of contact	Up to 160
Pitch	2.54 mm between rows - 1.27 mm between quicuncial contacts
Rows	3

Materials & Platings

Contact	Brass or bronze	
Moulding	Glass fiber filled diallyl - Phtalate	
Guides	Stainless steel or nickel plated brass	
	Standard	ESA
Pin body	0.25 µm gold / 1.27 µm Ni	1.27 µm gold / 1.27 µm Ni (min)
Socket body	0.25 µm gold / 1.27 µm Ni on active area 1.27 µm Ni on non active area	0.25 µm gold / 1.27 µm Ni (min)
Socket wires	1 µm gold / 0.20 µm Ni	1.27 µm gold / 0.20 µm Ni (min)

Electrical

Current grade rating (at 25°C)	Standard grade: 3 A max. - ESA grade: 5 A max.
Dielectric withstanding voltage	1200 Vrms
Contact resistance	≤8 mΩ
Insulation resistance	>104 MΩ (500 Vcc)

Mechanical

Mating & unmating cycle	5000
Guiding	By two outside guides (2 guiding styles) and one central guide (3 guiding styles)
Keying	By rotating of outside polarised guides (up to 36 keying)

Environmental

Temperature range	-55°C to 125°C
Conformity	MIL C 55302, ESA/ESCC3401/016 - 3401/017, NF C-UTE C 93-424

How To Order



1	Series																																					
2	Pitch or type	N 1.27 mm pitch, rear removable contacts																																				
3	Model	C 3 rows centered fixing D 3 rows uncentered fixing																																				
4	Number of contacts	KNC 062 080 098 160 KND 026 044 062 080 098 108 126 144																																				
5	Moulding polarity	NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE NF C-UTE C 93-424 MIL-C-55302 ESA/ESCC 3401/01601B SPACE GRADE 12 14 54 54 Female plug 13 15 55 55 Male plug 16 18 56 56 Tinned female plug*[†] 17 19 57 57 Tinned male plug*[†] 1A 1C 5A 5A Tinned female plug**[†] 1B 1D 5B 5B Tinned male plug**[†] 22 24 44 44 Female receptacle 23 25 45 45 Male receptacle 26 28 46 46 Tinned female receptacle*[†] 27 29 47 47 Tinned male receptacle*[†] 2A 2C - - Tinned female receptacle**[†] 2B 2D - - Tinned male receptacle**[†]																																				
6	Termination styles	10 Through board solder - 90° - length 3 mm 11 Through board solder - 90° - length 4 mm 12 Through board solder - 90° - length 4.50 to 5.2 mm 20 Crimp 21 Double Crimp 30 Through board solder - straight 40 Solder bucket 40 Solder bucket 51 Wire wrap (3 wrapping levels) 90 Male - male 91 Female - male																																				
7	Mounting hardware	Guide Style (consult us for special guides) <table> <tr> <td>110 Male polarised, transverse mount, standard plug</td> <td>145 Male polarised, transverse mount on receptacle only</td> <td>131 Male unpolarised, transverse mount</td> </tr> <tr> <td>111 Male polarised, vertical mount</td> <td>190 Female power or mass contact, vertical mount</td> <td>132 Female unpolarised, transverse mount</td> </tr> <tr> <td>113 Male polarised, float mount</td> <td>125 Male unpolarised, transverse mount</td> <td>133 Female all polarised, transverse mount</td> </tr> <tr> <td>121 Female polarised, vertical mount</td> <td>126 Female unpolarised, vertical mount</td> <td>191 Male power or mass contact, vertical mount</td> </tr> <tr> <td>123 Female polarised, float mount</td> <td>127 Male unpolarised, vertical mount</td> <td></td> </tr> <tr> <td>124 Female polarised, transverse mount</td> <td>130 Female unpolarised, vertical mount</td> <td></td> </tr> </table> Locking Styles <table> <tr> <td>MALE PLUG</td> <td>FEMALE RECEPTACLE</td> <td></td> </tr> <tr> <td>201 1/4 turn, free connector</td> <td>202 1/4 turn, vertical mount</td> <td>212 Jackscrew, transverse mount</td> </tr> <tr> <td>203 1/4 turn, transverse mount</td> <td>204 1/4 turn, transverse mount</td> <td>215 Jackscrew, vertical mount</td> </tr> <tr> <td>207 Jackscrew, free connector</td> <td>208 Jackscrew, transverse mount</td> <td>219 Jackscrew, vertical mount</td> </tr> <tr> <td>211 Jackscrew, free connector</td> <td>210 Jackscrew, free connector</td> <td>232 Jackscrew, with operation button</td> </tr> <tr> <td>290 Jackscrew, vertical mount</td> <td></td> <td></td> </tr> </table>	110 Male polarised, transverse mount, standard plug	145 Male polarised, transverse mount on receptacle only	131 Male unpolarised, transverse mount	111 Male polarised, vertical mount	190 Female power or mass contact, vertical mount	132 Female unpolarised, transverse mount	113 Male polarised, float mount	125 Male unpolarised, transverse mount	133 Female all polarised, transverse mount	121 Female polarised, vertical mount	126 Female unpolarised, vertical mount	191 Male power or mass contact, vertical mount	123 Female polarised, float mount	127 Male unpolarised, vertical mount		124 Female polarised, transverse mount	130 Female unpolarised, vertical mount		MALE PLUG	FEMALE RECEPTACLE		201 1/4 turn, free connector	202 1/4 turn, vertical mount	212 Jackscrew, transverse mount	203 1/4 turn, transverse mount	204 1/4 turn, transverse mount	215 Jackscrew, vertical mount	207 Jackscrew, free connector	208 Jackscrew, transverse mount	219 Jackscrew, vertical mount	211 Jackscrew, free connector	210 Jackscrew, free connector	232 Jackscrew, with operation button	290 Jackscrew, vertical mount		
110 Male polarised, transverse mount, standard plug	145 Male polarised, transverse mount on receptacle only	131 Male unpolarised, transverse mount																																				
111 Male polarised, vertical mount	190 Female power or mass contact, vertical mount	132 Female unpolarised, transverse mount																																				
113 Male polarised, float mount	125 Male unpolarised, transverse mount	133 Female all polarised, transverse mount																																				
121 Female polarised, vertical mount	126 Female unpolarised, vertical mount	191 Male power or mass contact, vertical mount																																				
123 Female polarised, float mount	127 Male unpolarised, vertical mount																																					
124 Female polarised, transverse mount	130 Female unpolarised, vertical mount																																					
MALE PLUG	FEMALE RECEPTACLE																																					
201 1/4 turn, free connector	202 1/4 turn, vertical mount	212 Jackscrew, transverse mount																																				
203 1/4 turn, transverse mount	204 1/4 turn, transverse mount	215 Jackscrew, vertical mount																																				
207 Jackscrew, free connector	208 Jackscrew, transverse mount	219 Jackscrew, vertical mount																																				
211 Jackscrew, free connector	210 Jackscrew, free connector	232 Jackscrew, with operation button																																				
290 Jackscrew, vertical mount																																						

- * For 90° & straight terminations (splicing on PCB)
- ** RoHS compliant for 90° & straight terminations (splicing on PCB)
- † Tinned contacts are not available as spares

Hypertac & ESA Correspondance Table

HYPERTAC **KNC**

34 01 016 01 B

1

2

3

4

5

6

1 ESCC component number

2 Mounting

3 Termination style

4 Locking type
On left side

5 Locking type
In center

6 Locking type
On right side

HYPERTAC

ESA

Plug KNB 017	01	Plug KNB 096	08	Receptacle KNB 053	16	Plug KNB 072	56	Plug KNC 098	62
Plug KNB 029	02	Plug KNB 120	10	Receptacle KNB 065	17	Receptacle KNB 072	57	Receptacle KNC 098	63
Plug KNB 041	03	Plug KNC 160	12	Receptacle KNB 084	19	Plug KNC 062	58		
Plug KNB 053	04	Receptacle KNB 017	13	Receptacle KNB 096	20	Receptacle KNC 062	59		
Plug KNB 065	05	Receptacle KNB 029	14	Receptacle KNB 120	22	Plug KNC 080	60		
Plug KNB 084	07	Receptacle KNB 041	15	Receptacle KNC 160	24	Receptacle KNC 080	61		

REMINDER SPATIAL P.P.P. (Party Polarity Protection)

Female receptacle	44	Plug female	54
Male receptacle	45	Plug male	55

EXAMPLE

KNC 062 44 30 113
P.P.P.

HYPERTAC

ESA

Bent male 10	MC	Solder bucket male 40	MS	Bent female tinned 10	FA	Mini-wrapping female 51	FY
Bent male tinned 10	MA	Mini-wrapping male 51	MY	Crimp female 20	FR	Bent long female 11	FL
Crimp male 20	MR	Bent long male 11	ML	Straight female 30	FD	Bent long female tinned 11	FG
Straight male 30	MD	Bent long male tinned 11	MG	Straight female tinned 30	FE	Female-male 91	FM
Straight male tinned 30	ME	Bent female 10	FC	Solder bucket female 40	FS		

HYPERTAC

ESA

Guideless connector	00	KNB	145	40	KNC	10 209	49	KNB	11 125	71	KNB	11 208	79	
KNB	131	31	KNB	124	41	KN	210	50	KNB	11 110	72	KN	219	80
KNB	132	32	KNC	10 230	43	KN	211	51	KNB	10 230	73	KN	290*	81
KNB	10 110	33	KN	232	45	KNB	212	52	KNC	124	74			
KNC	10 110	34	KN	231	46	KN	215	53	KNC	132	75			
KN	111	35	KN	207	47	KN	123	54	KNC	11 110	76			
KN	121	36	KNB	10 208	48	KN	113	55	KNC	11 125	77			

00 For 2 guide connectors

- - For 3 guide connectors (see table 4, Locking type - On left side)

HYPERTAC

ESA

KNB	10 125	26	KNC	10 125	27	KN	127	28	KN	126	29
-----	--------	----	-----	--------	----	----	-----	----	----	-----	----

(see table 4, Locking type - On left side)

Please consult us

Contact Terminations

Plug

Male





Female

Receptacle





Male

Female





90° Through board solder

Ref: **10** (X=3)Ref: **11** (X=4)Ref: **12** (X= 4.50 mm min to 5.70 mm max)Ref: **13** (X= 4.50 mm min to 5.70 mm max)





Crimp (AWG 28-22)

Ref: **20**Ref: **21** (MR & FR)

Crimp (AWG 28-22)

Ref: **21**

Straight through board solder

Ref: **30**Ref: **31** (MD & FD/ ME & FE)

Contact Terminations





Plug

Male

Female

Solder bucket (AWG 22 max)

Ref: **40** Ref : **MS & FS**







Receptacle

Male

Female



Wire wrap (3 wrapping levels)

Ref: **51** Ref : **MY & FY**





Saver (male-male)

Ref: **90**




Saver (female-male)

Ref: **91** Ref : **FM**




Dimensions

Plug





Receptacle

26 to 98 contacts



108 to 160 contacts



		No. of contacts	26	44	62	80	98	108	126	144	160
KNC	Plug & Receptacle	A	–	–	60.96	76.20	91.44	–	–	–	149.86
		B max	–	–	69.00	84.20	99.50	–	–	–	158.00
	Plug	C max	–	–	9.45	9.45	9.45	–	–	–	9.30
		D	–	–	4.42	4.42	4.42	–	–	–	4.70
	Receptacle	C max	–	–	9.30	9.30	9.30	–	–	–	9.30
		D	–	–	4.17	4.17	4.17	–	–	–	4.70
KND	Plug & Receptacle	A	30.48	45.72	60.96	76.20	91.44	106.68	121.92	137.16	–
		B max	38.50	53.70	69.00	84.20	99.50	114.70	129.90	145.20	–
	Plug	C min	8.95	8.95	8.95	8.95	8.95	8.95	8.95	8.95	–
		C max	9.55	9.55	9.55	9.55	9.55	9.55	9.55	9.55	–
		D	3.15	3.15	3.15	3.15	3.15	3.15	3.15	3.15	–
	Receptacle	C max	9.35	9.35	9.35	9.35	9.35	9.35	9.35	9.35	–
		D	3.10	3.10	3.10	3.10	3.10	3.10	3.10	3.10	–

Guide Device and Polarity Termination Compatibility Chart

Compatible
Compatible special saver connector

FP = Female Plug

FR = Female Receptacle

MR = Male Receptacle

[illegible]


Guide Styles

Plug & Receptacle

Male

Polarised vertical mount


Ref: **111** Ref : **35**



Female


Polarised vertical float mount

Ref: **123** Ref : **54**




Polarised vertical float mount

Ref: **113** Ref : **55**




Polarised transverse mount

Ref: **124** Ref : **74**
KNC X=11.20 Y=14.00 KND X=12.80 Y=15.90




Unpolarised vertical mount

Ref: **127** Ref : **28**




Unpolarised vertical mount

Ref: **126** Ref : **29**




Unpolarised transverse mount

Ref: **131**
KNC X=11.20 Y=14.00 KND X=12.80 Y=15.90



All polarised vertical mount

Ref: **130**



 Ref. applies only to the KNC Series

Guide Styles


Plug & Receptacle

Male

Polarised transverse mount

Ref: **145**

KNC X=11.20 Y=14.00 **KND** X=12.80 Y=15.90




Female

Unpolarised transverse mount


Ref: **132** Ref: **75**

KNC X=11.20 Y=14.00 **KND** X=12.80 Y=15.90



Polarised vertical mount


Ref: **121** Ref: **36**



All polarised transverse mount

Ref: **133**

KNC X=11.20 Y=14.00 **KND** X=12.80 Y=15.90




Guide Styles

Plug & Receptacle

Male

Power or mass vertical mount


Ref: **191** PCB thickness **1.60**



Female

Power or mass vertical mount

Ref: **190**




Male plug only

KNC only


Polarised transverse mount

Ref: **10 110** Ref: **34** PCB thickness **1.60** Y=3.65
 Ref: **11 110** Ref: **34** PCB thickness **2.40** Y=5.65
 Ref: **12 110** PCB thickness **3.20** Y=5.65



Unpolarised transverse mount


Ref: **10 125** Ref: **27** PCB thickness **1.60** Y=3.65
 Ref: **11 125** Ref: **27** PCB thickness **1.60** Y=5.65
 Ref: **12 125** PCB thickness **1.60** Y=5.65



KND only


Polarised transverse mount

Ref: **10 110** X=1.60 Y=3.20
 Ref: **11 110** X=2.40 Y=4.90
 Ref: **12 110** X=3.20 Y=6.90



Unpolarised transverse mount

Ref: **10 125** X=1.60 Y=3.20
 Ref: **11 125** X=2.40 Y=4.90
 Ref: **12 110** X=3.20 Y=6.90



© Ref. applies only to the KNC Series


Locking Devices Compatibility Chart

[illegible]


Male Locking Styles

Plug & Receptacle


Jack 1/4 turn lock, free connector

Ref: **201**


Jackscrew, free connector

Ref: **211** Ref: **51**


Jack 1/4 turn lock, transverse mount

Ref: **206**


Jackscrew, vertical mount

Ref: **231** Ref: **46**

Jackscrew, free connector

Ref: **207** Ref: **47**

Jackscrew, vertical mount


Ref: **290** Ref: **81**

Female Locking Styles

Plug & Receptacle

Jack 1/4 turn lock, vertical mount


Ref: **202**



Jackscrew, transverse mount


Ref: **212**

KNC X=11.20 Y=14.00 **KND** X=12.80 Y=15.90




Jackscrew, transverse mount

Ref: **10 209** Ref : **49** PCB thickness 1.60




Jackscrew, vertical mount

Ref: **215** Ref : **53**




Jackscrew, free connector

Ref: **210** Ref : **50**




Jackscrew, vertical mount

Ref: **219** Ref : **80**




Rotating jackscrew

Ref: **232**




Receptacle Mating Side Layout View

26 to 98 contacts




108 to 160 contacts




Panel Preparation Details

26 to 98 contacts



108 to 160 contacts



Panel: female or male, plug or receptacle

Terminations: 40 - 51

Guide styles: 111 - 121 (Fixed Mount)


Guide styles: 113 - 123 - 202 (Float Mount)

No. of contacts	26	44	62	80	98	108	126	144	160
A	30.48	45.72	60.96	76.20	91.44	106.68	121.92	137.16	149.86
B min	25.90	41.10	56.40	71.60	86.90	48.50	56.00	63.60	69.95
C (KNC)	—	—	6.00	6.00	6.00	—	—	—	6.00
C (KND)	4.73	4.73	4.73	4.73	4.73	4.73	4.73	4.73	—

Contacts


Male

Crimp terminations awg 22-28 (0.079 - 0.34 mm²)




Reference	Part number
KN- ---13 20 ---	006 042 1- 20R OG
KN- ---55 20 --- MR	006 042 1- 20P OF 3401 017 004B

Female




Reference	Part number
KN- ---22 20 ---	006 042 2- 20R G0
KN- ---44 20 --- FR	006 042 2- 20P J9 3401 017 015B

Crimp terminations awg 22-28 (0.079 - 0.34 mm²) & Sheath Ø1.45



Reference	Part number
KN- ---13 20 ---	006 063 1- 21R OG
KN- ---55 20 ---	006 063 1- 20R OF



Reference	Part number
KN- ---22 20 ---	006 063 2- 21R G0
KN- ---44 20 ---	006 063 2- 21R J3


Tools

Crimp tool & Positioner




Contact part number		Crimp tool	AWG	Wire cross section	Positioner	Tool turret	Selector position
006 042 1- 20R OG 006 042 2- 20R GO		ASTRO TOOL M22520/2.01	28	0.079	SS-0060000001		3
			26	0.14			4
			24	0.20			4
			22	0.34			5
		DANIELS M22520/2.01	28	0.079	SS-0060000001		3
			26	0.14			4
			24	0.20			4
			22	0.34			5
006 063 1- 21R OG 006 063 2- 21R GO	2 operations	ASTRO TOOL M22520/2.01	28	0.079	SS-0060000001		3
			26	0.14			4
			24	0.20			4
			22	0.34			5
		DANIELS M22520/2.01	28	0.079	SS-0060000001		3
			26	0.14			4
			24	0.20			4
			22	0.34			5
	1 st crimp (lead)	ASTRO TOOL M22520/2.01	28	0.079	SS-0060000002		*
			26	0.14			6
			24	0.20			7
			22	0.34			7
		DANIELS M22520/2.01	28	0.079	SS-0060000002		*
			26	0.14			6
			24	0.20			7
			22	0.34			7
	2 nd crimp (sheath)	52007	28	0.079		SP717	2
			26	0.14			3
			24	0.20			4
			22	0.34			4

Insertion



SM-0060000001

Extraction



SD-0060000006

Alignment Combs

for 90° through board termination


2 fixing points HPF107/B
3 fixing points SP. 006 00 00 004

Screwdriver for m3 nut

208 locking devices
215 locking devices
S_075

Accessories

Antistatic Pin Protector



Ordering information

K N B - - - _ 314

Ref

Use	A	Ref
KNB 017	24.13	009
KND 026		
KNB 029 KND 044	39.37	015
KNB 072 KND 108	46.99	018
KNB 041 & 084 KNC 062 KND 062 & 126	54.61	021


Use	A	Ref
KNB 096	62.23	024
KND 144		
KNB 053 KNC 080 & 160 KND 080	69.85	027
KNB 120	77.47	030
KNB 065 KNC 098 KND 098	83.82	033

Note: Each part number contains only one header.

To equip fully the connector, you have to order 2, 3, 4 or 6 identical headers.
Header can fit on contacts or be positionned between rows.

Accessories

Pin Protector (extruded polypropylene)



Ordering information
K N - - - - 308
B, C or D Number of positions

KNB	017	029	041	053	065	072	084	096	120
X ± 0.30	25.50	40.70	56	71.20	86.50	48.40	56	63.60	78.80
Qty	1	1	1	1	1	2	2	2	2

KNC	062	080	098	119	160
X ± 0.30	66	81.20	96.40	114.20	155.00
Qty	1	1	1	1	1

KND	026	044	108	126	144
X ± 0.30	35.50	50.70	111.70	127.00	142.20
Qty	1	1	1	1	1

Technical Characteristics

Contact diameter	HYPERTAC® type Ø 0.50 mm
Number of contact	Up to 162
Pitch	1.905 mm between rows - 1.27 mm between quicuncial contacts
Rows	3

Materials & Platings

Contact	Brass or bronze	
Moulding	Glass fiber filled diallyl - Phtalate	
Guides	Stainless steel or nickel plated brass	
	Standard	ESA
Pin body	0.25 µm gold / 1.27 µm Ni	1.27 µm gold / 1.27 µm Ni (min.)
Socket body	0.25 µm gold / 1.27 µm Ni on active area 1.27 µm Ni on non active area	0.25 µm gold / 1.27 µm Ni (min.)
Socket wires	1 µm gold / 0.20 µm Ni	1.27 µm gold / 0.20 µm Ni (min.)

Electrical

Current rating (at 25°C)	3 A max.
Dielectric withstanding voltage	800 Vrms
Contact resistance	≤8 mΩ
Insulation resistance	>10 ⁴ MΩ (500 Vcc)

Mechanical

Mating & unmating cycle	5000
Guiding	By two outside guides (2 guiding styles) and one central guide (3 guiding styles)
Keying	By rotating of outside polarised guides (up to 16 keying)

Environmental

Temperature range	-55°C to 125°C
Conformity	ESA/ESCC3401/016 - 3401/017, NF C-UTE C 93-424

How To Order



Hypertac & ESA Correspondance Table

ESA 3401/039 01B

K M C

1

2

3

4

5

1	Series																																																																										
2	Number of contacts	0 2 6	0 4 4	0 6 2	0 8 0	0 9 8	1 4 4	1 6 2																																																																			
3	Moulding polarity	NF C-UTE C 93-424 Ⓒ ESA/ESCC 3401/03901B SPACE GRADE <table><tr><td>12</td><td>-</td><td>54</td><td>Female plug</td></tr><tr><td>13</td><td>55</td><td>55</td><td>Male plug</td></tr><tr><td>16</td><td>-</td><td>56</td><td>Tinned female plug*</td></tr><tr><td>17</td><td>-</td><td>57</td><td>Tinned male plug*</td></tr></table>		12	-	54	Female plug	13	55	55	Male plug	16	-	56	Tinned female plug*	17	-	57	Tinned male plug*	NF C-UTE C 93-424 Ⓒ ESA/ESCC 3401/03901B SPACE GRADE <table><tr><td>1A</td><td>-</td><td>-</td><td>Tinned female plug**</td></tr><tr><td>1B</td><td>-</td><td>-</td><td>Tinned male plug**</td></tr><tr><td>22</td><td>44</td><td>44</td><td>Female receptacle</td></tr><tr><td>23</td><td>-</td><td>45</td><td>Male receptacle</td></tr></table>		1A	-	-	Tinned female plug**	1B	-	-	Tinned male plug**	22	44	44	Female receptacle	23	-	45	Male receptacle	NF C-UTE C 93-424 Ⓒ ESA/ESCC 3401/03901B SPACE GRADE <table><tr><td>26</td><td>-</td><td>46</td><td>Tinned female receptacle*</td></tr><tr><td>27</td><td>-</td><td>47</td><td>Tinned male receptacle*</td></tr><tr><td>2A</td><td>-</td><td>-</td><td>Tinned female receptacle**</td></tr><tr><td>2B</td><td>-</td><td>-</td><td>Tinned male receptacle**</td></tr></table>		26	-	46	Tinned female receptacle*	27	-	47	Tinned male receptacle*	2A	-	-	Tinned female receptacle**	2B	-	-	Tinned male receptacle**																				
12	-	54	Female plug																																																																								
13	55	55	Male plug																																																																								
16	-	56	Tinned female plug*																																																																								
17	-	57	Tinned male plug*																																																																								
1A	-	-	Tinned female plug**																																																																								
1B	-	-	Tinned male plug**																																																																								
22	44	44	Female receptacle																																																																								
23	-	45	Male receptacle																																																																								
26	-	46	Tinned female receptacle*																																																																								
27	-	47	Tinned male receptacle*																																																																								
2A	-	-	Tinned female receptacle**																																																																								
2B	-	-	Tinned male receptacle**																																																																								
4	Termination styles	<table><tr><td>Ⓒ 10</td><td>90° lenght 3 mm ("A" moulding)</td></tr><tr><td>10</td><td>90° lenght 3 mm ("B" moulding)</td></tr><tr><td>11</td><td>90° lenght 4 mm ("A" moulding)</td></tr><tr><td>13</td><td>90° lenght 5.5 mm ("B" moulding)</td></tr></table>		Ⓒ 10	90° lenght 3 mm ("A" moulding)	10	90° lenght 3 mm ("B" moulding)	11	90° lenght 4 mm ("A" moulding)	13	90° lenght 5.5 mm ("B" moulding)	<table><tr><td>Ⓒ 30</td><td>Through board solder - straight - lenght 4.5 mm</td></tr><tr><td>Ⓒ 31</td><td>Through board solder - straight - lenght 5.6 mm</td></tr><tr><td>Ⓒ 40</td><td>Solder bucket</td></tr><tr><td>50</td><td>Wire wrap (2 wrapping levels)</td></tr></table>		Ⓒ 30	Through board solder - straight - lenght 4.5 mm	Ⓒ 31	Through board solder - straight - lenght 5.6 mm	Ⓒ 40	Solder bucket	50	Wire wrap (2 wrapping levels)	<table><tr><td>Ⓒ 51</td><td>Wire wrap (3 wrapping levels)</td></tr><tr><td>90</td><td>Male - Female</td></tr><tr><td>Ⓒ 91</td><td>Female - male</td></tr></table>		Ⓒ 51	Wire wrap (3 wrapping levels)	90	Male - Female	Ⓒ 91	Female - male																																														
Ⓒ 10	90° lenght 3 mm ("A" moulding)																																																																										
10	90° lenght 3 mm ("B" moulding)																																																																										
11	90° lenght 4 mm ("A" moulding)																																																																										
13	90° lenght 5.5 mm ("B" moulding)																																																																										
Ⓒ 30	Through board solder - straight - lenght 4.5 mm																																																																										
Ⓒ 31	Through board solder - straight - lenght 5.6 mm																																																																										
Ⓒ 40	Solder bucket																																																																										
50	Wire wrap (2 wrapping levels)																																																																										
Ⓒ 51	Wire wrap (3 wrapping levels)																																																																										
90	Male - Female																																																																										
Ⓒ 91	Female - male																																																																										
5	Mounting hardware	Guide Styles (consult us for special guides) <table><tr><td>Ⓒ 110</td><td>Male polarised, transverse mount⁽¹⁾</td><td>127</td><td>Male unpolarised, vertical mount⁽²⁾</td><td>156</td><td>Male unpolarised, transverse mount⁽²⁾</td></tr><tr><td>111</td><td>Male polarised, vertical mount⁽²⁾</td><td>128</td><td>Male unpolarised, float mount⁽²⁾</td><td>173</td><td>Female unpolarised, transverse mount⁽¹⁾</td></tr><tr><td>112</td><td>Male polarised, vertical mount⁽²⁾</td><td>130</td><td>Female unpolarised, vertical mount⁽²⁾</td><td>174</td><td>Female polarised, transverse mount⁽¹⁾</td></tr><tr><td>113</td><td>Male polarised, float mount⁽²⁾</td><td>133</td><td>Female unpolarised, transverse mount⁽²⁾</td><td>190</td><td>Female power or mass contact, vertical mount</td></tr><tr><td>Ⓒ 121</td><td>Female polarised, vertical mount⁽²⁾</td><td>Ⓒ 143</td><td>Female polarised, vertical mount⁽²⁾</td><td>191</td><td>Male power or mass contact, transverse mount</td></tr><tr><td>123</td><td>Female polarised, float mount⁽²⁾</td><td>153</td><td>Female unpolarised, transverse mount⁽²⁾</td><td>Ⓒ 703</td><td>Female - male unpolairised guide ⁽¹⁾</td></tr><tr><td>124</td><td>Female polarised, transverse mount⁽²⁾</td><td>154</td><td>Female polarised, transverse mount⁽²⁾</td><td></td><td></td></tr><tr><td>125</td><td>Male unpolarised, transverse mount⁽¹⁾</td><td>155</td><td>Male unpolarised, transverse mount⁽²⁾</td><td></td><td></td></tr></table> Locking Styles <table><tr><th colspan="2">FEMALE</th><th colspan="2">MALE</th></tr><tr><td>Ⓒ 202</td><td>Jackscrew, vertical mount⁽²⁾</td><td>Ⓒ 201</td><td>Jackscrew, free connector⁽²⁾</td></tr><tr><td>203</td><td>Jackscrew, transverse mount</td><td>205</td><td>Jackscrew, transverse mount⁽¹⁾</td></tr><tr><td>Ⓒ 204</td><td>Jackscrew, transverse mount⁽²⁾</td><td>Ⓒ 206</td><td>Jackscrew, free connector⁽²⁾</td></tr><tr><td>207</td><td>Jackscrew, vertical mount⁽²⁾</td><td></td><td></td></tr></table>						Ⓒ 110	Male polarised, transverse mount ⁽¹⁾	127	Male unpolarised, vertical mount ⁽²⁾	156	Male unpolarised, transverse mount ⁽²⁾	111	Male polarised, vertical mount ⁽²⁾	128	Male unpolarised, float mount ⁽²⁾	173	Female unpolarised, transverse mount ⁽¹⁾	112	Male polarised, vertical mount ⁽²⁾	130	Female unpolarised, vertical mount ⁽²⁾	174	Female polarised, transverse mount ⁽¹⁾	113	Male polarised, float mount ⁽²⁾	133	Female unpolarised, transverse mount ⁽²⁾	190	Female power or mass contact, vertical mount	Ⓒ 121	Female polarised, vertical mount ⁽²⁾	Ⓒ 143	Female polarised, vertical mount ⁽²⁾	191	Male power or mass contact, transverse mount	123	Female polarised, float mount ⁽²⁾	153	Female unpolarised, transverse mount ⁽²⁾	Ⓒ 703	Female - male unpolairised guide ⁽¹⁾	124	Female polarised, transverse mount ⁽²⁾	154	Female polarised, transverse mount ⁽²⁾			125	Male unpolarised, transverse mount ⁽¹⁾	155	Male unpolarised, transverse mount ⁽²⁾			FEMALE		MALE		Ⓒ 202	Jackscrew, vertical mount ⁽²⁾	Ⓒ 201	Jackscrew, free connector ⁽²⁾	203	Jackscrew, transverse mount	205	Jackscrew, transverse mount ⁽¹⁾	Ⓒ 204	Jackscrew, transverse mount ⁽²⁾	Ⓒ 206	Jackscrew, free connector ⁽²⁾	207	Jackscrew, vertical mount ⁽²⁾		
Ⓒ 110	Male polarised, transverse mount ⁽¹⁾	127	Male unpolarised, vertical mount ⁽²⁾	156	Male unpolarised, transverse mount ⁽²⁾																																																																						
111	Male polarised, vertical mount ⁽²⁾	128	Male unpolarised, float mount ⁽²⁾	173	Female unpolarised, transverse mount ⁽¹⁾																																																																						
112	Male polarised, vertical mount ⁽²⁾	130	Female unpolarised, vertical mount ⁽²⁾	174	Female polarised, transverse mount ⁽¹⁾																																																																						
113	Male polarised, float mount ⁽²⁾	133	Female unpolarised, transverse mount ⁽²⁾	190	Female power or mass contact, vertical mount																																																																						
Ⓒ 121	Female polarised, vertical mount ⁽²⁾	Ⓒ 143	Female polarised, vertical mount ⁽²⁾	191	Male power or mass contact, transverse mount																																																																						
123	Female polarised, float mount ⁽²⁾	153	Female unpolarised, transverse mount ⁽²⁾	Ⓒ 703	Female - male unpolairised guide ⁽¹⁾																																																																						
124	Female polarised, transverse mount ⁽²⁾	154	Female polarised, transverse mount ⁽²⁾																																																																								
125	Male unpolarised, transverse mount ⁽¹⁾	155	Male unpolarised, transverse mount ⁽²⁾																																																																								
FEMALE		MALE																																																																									
Ⓒ 202	Jackscrew, vertical mount ⁽²⁾	Ⓒ 201	Jackscrew, free connector ⁽²⁾																																																																								
203	Jackscrew, transverse mount	205	Jackscrew, transverse mount ⁽¹⁾																																																																								
Ⓒ 204	Jackscrew, transverse mount ⁽²⁾	Ⓒ 206	Jackscrew, free connector ⁽²⁾																																																																								
207	Jackscrew, vertical mount ⁽²⁾																																																																										


(1) Moulding A - (2) Moulding B

- * For 90° & straight terminations (splicing on PCB)
- ** RoHS compliant for 90° & straight terminations (splicing on PCB)


Moulding Styles

Plug

One Part (moulding A)




- Fitted with male contacts**
- 90° through board solder




- Fitted with male contacts**
- 90° through board solder
(same design as the "A" plug type but printed as receptacle)


Two Parts (moulding B)




- Fitted with male contacts (pins)**
- Straight through board solder
 - Wire wrap type
(2 and 3 wrapping levels)
 - Solder bucket




- Fitted with female contacts**
- Straight through board solder
 - Wire wrap type
(2 and 3 wrapping levels)
 - Solder bucket
(same design as the "B" plug type but printed as receptacle)



- Fitted with female contacts (sockets)**
- 90° through board solder
Note: the spacing of the rows for board preparation is different to the spacing of the plug fitted with the 90° termination
 - Straight through board solder
 - Wire wrap type
(2 and 3 wrapping levels)
 - Solder bucket



- Fitted with female contacts (sockets)**
- 90° through board solder
Note: the spacing of the rows for board preparation is different to the spacing of the plug fitted with the 90° termination




- Fitted with male contacts (pins)**
- Straight through board solder
 - Wire wrap type
(2 and 3 wrapping levels)
 - Solder bucket
(same design as the "B" plug type but printed as receptacle)

Contact Terminations

Plug

Male




Moulding "A"

Female


90° Through board solder

Ref: 10 Ref : 10 (only A Moulding)



Moulding "B"


Male



Moulding "B"

Receptacle





Female



Moulding "A"





90° through board solder

Moulding A Ref: 11 (X=4.00) Moulding B Ref: 13 (X=5.50)







Straight through board solder

Ref: 30 (X=4.50) Ref : 30 Ref: 31 (X=5.60) Ref : 31



Solder bucket (AWG 26 max)

Ref: 40 Ref : 40



Note: moulding A and B need different preparation board details for 90° tail termination.





Contact Terminations

Plug





Male

Female

Wire wrap (2 wrapping levels)



Ref: 50 Ref : 50

Wire wrap (3 wrapping levels)



Ref: 51 Ref : 51

Saver (Male-Male)

Ref: 90



Saver (Female-Male)

Ref: 91 Ref : 91

Note: moulding A and B need different preparation board details for 90° tail termination.



Dimensions

26 to 98 Contacts

144 to 162 Contacts



One Part (moulding A)

90° male plug KMC ... 13 10 ...
90° male receptacle KMC ... 23 10 ...



Two parts (moulding B)

Female or male receptacle KMC ... 2. ...
Female or male plug KMC ... 1. ...



No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B max	38.50	53.70	69.00	84.20	99.50	145.20	160.40
C	20.32	35.56	50.80	66.04	81.28	58.42	66.04

Legend														Polarity												
Compatible														All pinning		A		Moulding								
Compatible special saver connector														All pinning		B										
FR 22	MP 12	MR 23	MP 13	MR 23	MP 13	FR 22	FP 12	FR 22	FP 12	FR 22	FP 12	MR 23	FR 22	FP 12	MP 13	FR 22	FP 12	MR 23	FR 22	FP 12	MP 13	90°	13F	11M	10	Contact
																						Straight		31	30	
																						Solder bucket			40	
																						Wire wrap		51	50	
																						Femal/male	Male/male	91	90	

MP 13

MR 23

FP 12

FR 22

FP 12

FR 22

FP 12

MP 13

MR 23

FR 22

MP 13

MR 23

FR 22

MP 13

MR 23

FR 22

MP 13

MR 23

90°

Straight

Solder bucket

Mini-wrap

Male-male

Female-male

A

B

13F

11m

10

31

30

40

51

50

90

Male or female

Male-male

Female-male

703

190

174

173

154

153

133

130

123

124

143/121

703

191

156

155

128

127

125

113

112

111


110

Female guides


Male guides

Male Guide Styles


Polarised transverse mount (moulding A)




Unpolarised transverse mount (moulding A) central guide (KMC 144-162)




Polarised vertical mount (moulding B)




Unpolarised vertical mount (moulding B) central guide (KMC 144-162)




Polarised vertical float mount (moulding B)



Unpolarised vertical float mount (moulding B) central guide (KMC 144-162)




Polarised vertical float mount (moulding B)




Male Guide Styles


Unpolarised transverse mount (moulding A)




Unpolarised transverse mount (moulding A) central guide (KMC 144-162)




Unpolarised vertical mount (moulding B)




Unpolarised vertical mount (moulding B) central guide (KMC 144-162)




Unpolarised transverse mount (moulding B)




Unpolarised transverse mount (moulding B) central guide (KMC 144-162)



Polarised transverse mount (moulding B)




Unpolarised transverse mount (Moulding B) central guide (KMC 144-162)



Female Guide Styles


Polarised vertical mount (moulding B)

Ref:  **121** Ref: **143** Ref:  **143**




Unpolarised vertical mount (moulding B)

central guide (KMC 144-162)




Polarised transverse mount (moulding B)

Ref: **124**




Unpolarised transverse mount (moulding B) central guide (KMC 144-162)




Polarised vertical float mount (moulding B)

Ref: **123**




All keying types (moulding B)

Ref: **130**




All keying types (moulding B) central guide (KMC 144-162)




Female Guide Styles


All keying types (moulding B)

Ref: **133**


All keying types (moulding B) central guide (KMC 144-162)




All keying types (moulding B)

Ref: **153**


All keying types (moulding B) central guide (KMC 144-162)



Polarised transverse mount (moulding B)

Ref: **154**


Unpolarised transverse mount (moulding B) central guide (KMC 144-162)




Guide Styles

Female

Unpolarised transverse mount
(moulding A)




Unpolarised transverse mount (moulding A)
central guide (KMC 144-162)




Polarised transverse mount
(moulding A)

Ref: 174




Unpolarised transverse mount
(moulding A) central guide (KMC 144-162)



Female

Mass and power contact
(moulding B)


Ref: 190



Male

Mass and power contact
(moulding A)


Ref: 191




Female - Male

Unpolarised transverse mount
(moulding B)





Ref: 703 Ref: 703



Unpolarised transverse mount
(moulding B) central guide (KMC 144-162)



Locking Device Compatibility chart

						A	Moulding
						B	
							206
							205
							201
					Male locking devices		
A	B				Female locking devices		
Moulding		204	203	202/207			

 Compatible

Note: the connector must be fitted with its locking devices before soldering on the PCB (straight through board solder):


- Connector on PCB: impossibility to change the keying.
- If you need to change the keying:
 - pierce PCB through Ø 3.70, fixing devices
 - use 054826.000R shouldered washer
 } (for 202 and 207)

Locking Styles

Male


Jackscrew, free connector (moulding B)

Ref: **201** Ref : **201**
For **KMC 144-162** the supplied central guide is Ref: **111**




Jackscrew, transverse mount (moulding A)

Ref: **205**
For **KMC 144-162** the supplied central guide is Ref: **110**



Jackscrew, free connector (moulding B)

Ref: **206** Ref : **206**
For **KMC 144-162** the supplied central guide is Ref: **112**



Locking Styles

Female


Non rotating jackscrew, vertical mount (moulding B)

Ref: **202** Ref: : **202**

For **KMC 144-162** jackscrew 202 the supplied central guide is Ref: **121**

Ref: **207**


jackscrew 207 the supplied central guide is Ref: **143**



Non rotating jackscrew, transverse mount (moulding A)

Ref: **203**


For **KMC 144-162** jackscrew 202 the supplied central guide is Ref: **173**



Non rotating jackscrew, transverse mount (moulding B)

Ref: **204** Ref: : **204**

For **KMC 144-162** the supplied central guide is Ref: **111**




Mating Side Layout View


Moulding A

Plug


Receptacle




026




044





062





080




098



144




162




Mating Side Layout View

Moulding B


Plug



026




044




062




080



098










144



162

Receptacle





Board Preparation Details

Two Parts (moulding B)

26 to 98 contacts



144 to 162 contacts

Mother board



Female or male, plug or receptacle, straight solder terminations 30 or 31
Guide styles: 111 - 112 - 121 - 127 - 130 - 143 - 190

Daughter board



Female or male, plug or receptacle, 90° termination
Guide styles: 153 - 154 - 155 - 156

No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B	20.32	35.56	50.80	66.04	81.28	58.42	66.04
C	17.78	33.02	48.26	63.50	78.74	-	-



Board Preparation Details

Two Parts (moulding B)

26 to 98 contacts

144 to 162 contacts

Daughter board



Female or male, plug or receptacle, 90° termination

Guide styles: 124 - 133


No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B	20.32	35.56	50.80	66.04	81.28	58.42	66.04
C	17.78	33.02	48.26	63.50	78.74	-	-

Board Preparation Details

One Part (moulding A)

Daughter board


26 to 98 Contacts



Male, plug or receptacle, 90° termination

Guide styles: 110 - 125 - 191 - 203 - 205

144 to 162 Contacts



Male, plug or receptacle, 90° termination

Guide styles: 110 - 125 - 191 - 205


No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B	20.32	35.56	50.80	66.04	81.28	58.42	66.04
C	17.78	33.02	48.26	63.50	78.74	—	—

Board Preparation Details

One Part (moulding A)

Daughter board

144 to 162 Contacts



Male, plug or receptacle, 90° termination

Locking styles: 203

No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B	20.32	35.56	50.80	66.04	81.28	58.42	66.04
C	17.78	33.02	48.26	63.50	78.74	–	–



Panel Preparation Details

Two Parts (moulding B)

26 to 98 contacts



144 to 162 contacts

Mother board



Plug or receptacle, 90° termination
Guide styles: 153 - 154 - 155 - 156

Daughter board



— Fixed mount --- Float mount (2 mm thickness)

Female or male, plug or receptacle, 90° termination 40 - 50 - 51
Guide styles: 111 - 112 - 121 - 127 - 130 - 143 - 190 - (Fixed Mount)
Guide styles: 113 - 123 - 128 - (Float Mount)
Locking Styles: 202 - 207

No. of contacts	26	44	62	80	98	144	162
A	30.48	45.72	60.96	76.20	91.44	137.16	152.40
B	20.32	35.56	50.80	66.04	81.28	58.42	66.04
C	17.78	33.02	48.26	63.50	78.74	-	-
D	25.90	41.20	56.40	71.60	86.90	63.60	71.60

Technical Characteristics

	Signal contact	Power contact	High frequency contact
Contact diameter	HC® Ø 0.50 mm	HC® Ø 2.00 mm	HE 807 type
Number of contact	Up to 162		
Pitch	1.905 mm between rows 1.27 mm between quicuncial contacts	5.08 on 1 row	
Rows	3		

Electrical

Current rating (at 25°C)	3 A max.	15 A	0.5 A
Dielectric withstanding voltage	800 Vrms		
Nominal voltage			180 Vrms 50 Hz
Impedance			50 Ω
Contact resistance	≤8 mΩ	≤2 mΩ	≤10 mΩ
Insulation resistance	104 MΩ (500 Vcc)		≥107 MΩ

Environmental

Temperature range		-55° C to 125° C	
Mating forces		FI ≤8N - FS ≤3N	1N ≤FI/FS ≤5N
Conformity		NF C-UTE C 93-424	


Materials & Platings

Contact	Brass or bronze		
Moulding	Glass fiber filled diallyl - Phtalate		
Guides	Stainless steel or nickel plated brass		
	Standard	ESA	
Pin body	0.25 µm gold / 1.27 µm Ni	1.27 µm gold / 1.27 µm Ni (min)	
Socket body	0.25 µm gold / 1.27 µm Ni on active area 1.27 µm Ni on activ area	0.25 µm gold / 1.27 µm Ni (min)	
Socket wires	1 µm gold / 0.20 µm Ni	1.27 µm gold / 0.20 µm Ni (min)	

Mechanical

Mating & unmating cycle	5000
Guiding	By two outside guides (2 guiding styles) and one central guide (3 guiding styles)
Keying	By rotating of outside polarised guides (up to 16 keying)


How To Order




1	Type	A H Moulding with cavities for special contacts B 3 6 Number of cavities for special contacts C 2 6 4 4 8 0 9 0 Number of signal contacts 0.50 mm																																						
2	Moulding polarity	NF C-UTE C 93-424 SPACE GRADE <table><tr><td>12</td><td>54</td><td>Female plug</td></tr><tr><td>13</td><td>55</td><td>Male plug</td></tr><tr><td>16</td><td>56</td><td>Tinned female plug*</td></tr><tr><td>17</td><td>57</td><td>Tinned male plug*</td></tr></table>	12	54	Female plug	13	55	Male plug	16	56	Tinned female plug*	17	57	Tinned male plug*	NF C-UTE C 93-424 SPACE GRADE <table><tr><td>1A</td><td>-</td><td>Tinned female plug**</td></tr><tr><td>1B</td><td>-</td><td>Tinned male plug**</td></tr><tr><td>22</td><td>44</td><td>Female receptacle</td></tr><tr><td>23</td><td>45</td><td>Male receptacle</td></tr></table>	1A	-	Tinned female plug**	1B	-	Tinned male plug**	22	44	Female receptacle	23	45	Male receptacle	NF C-UTE C 93-424 SPACE GRADE <table><tr><td>26</td><td>46</td><td>Tinned female receptacle*</td></tr><tr><td>27</td><td>47</td><td>Tinned male receptacle*</td></tr><tr><td>2A</td><td>-</td><td>Tinned female receptacle**</td></tr><tr><td>2B</td><td>-</td><td>Tinned male receptacle**</td></tr></table>	26	46	Tinned female receptacle*	27	47	Tinned male receptacle*	2A	-	Tinned female receptacle**	2B	-	Tinned male receptacle**
12	54	Female plug																																						
13	55	Male plug																																						
16	56	Tinned female plug*																																						
17	57	Tinned male plug*																																						
1A	-	Tinned female plug**																																						
1B	-	Tinned male plug**																																						
22	44	Female receptacle																																						
23	45	Male receptacle																																						
26	46	Tinned female receptacle*																																						
27	47	Tinned male receptacle*																																						
2A	-	Tinned female receptacle**																																						
2B	-	Tinned male receptacle**																																						
3	Termination styles	(see KMC ordering information p. 43)																																						
4	Mounting hardware	Guide Styles (see p. 50 to 54) - (Consult us for special guides) - See KMC ordering information p. 43 Locking Styles (see p. 56-57) - See KMC ordering information p. 43																																						

* For 90° & straight terminations (splicing on PCB)
** RoHS conform for 90° & straight terminations (splicing on PCB)

Layout



No. of fixings	KMH layout	No. of special contact cavities	No. of signal contacts
2	326	3	26
2	344	3	44
2	380	3	80
3	390	3	90




KMH layout	No. of special contact cavities	No. of signal contacts	KMH layout equivalent dimensions
			044
626	6	26	062
			098
			108

Dimensions

26 to 80 Signal Contacts & 3 Special contact cavities


One part plug (moulding A)

only KMH 380




Two parts plug & receptacle (moulding B)

KMH 326, 344, 380



90 Signal Contacts & 3 Special contact cavities


Two parts plug & receptacle (moulding B) KMH 390



KMH layout	A	B max	C	D	E	KMH layout equivalent dimensions
326	45.72	53.70	35.56	20.32	17.78	044
344	60.96	69.00	50.80	35.56	33.02	062
380	91.44	99.50	81.28	66.04	63.50	098
390	106.68	114.70	96.52	43.18	27.94	108

26 Signal Contacts & 6 Special contact cavities


Two parts plug & receptacle (moulding B) with special contact cavities on both extremities
KMH 626



Power & High Frequency Contacts

(NF C-UTE C 93-569)

Example of contact overview (020 084 2- 10 RN1)




Male	P/N	Female	P/N
90° termination	020 085 1- 10R OG	90° termination	020 084 2- 10R G1
Straight termination	020 087 1- 30R OG	Straight termination	020 056 2- 30R G1
Solder bucket termination	020 091 1- 40R OG	Solder bucket termination	020 060 2- 40R G1

Tools and Accessories

Screwdrivers

Reference	Use	Pinning			Remark
S_____028	- Connector fitted with female guides - "B" moulding - Cover's fixing screw for female guide	144	to	162	These three screwdrivers can be delivered in a same packing under the reference S_____036
S_____029	- Connector fitted with male guides - "B" moulding - Cover's fixing screw for female guide and screw central fixing on wiring side	144	to	162	
S_____033	- "B" moulding - Cover's fixing screws	026	to	162	

Special contact extraction tool




SD.030 00 CX 003

Pin protector

Reference	Use	Guide style
KMC..._____302* Pinning	KMC... 13..110-KMC...23..111 KMC ... 13..111	Polarised male guide
KMC..._____303* Pinning	KMC... 13..125	Unpolarised male guide
KMC..._____304* Pinning	KMC... 23..153	Unpolarised female guide
KMC..._____305* Pinning	KMC... 23..121 KMC... 23..154	Polarised female guide

Note: these 4 references are not available for the 162 contacts version
 • Antistatic material



Notes:

Disclaimer

All of the information included in this catalogue is believed to be accurate at the time of printing. It is recommended, however, that users should independently evaluate the suitability of each product for their intended application and be sure that each product is properly installed, used and maintained to achieve desired results.

Smiths Interconnect, a Molex company, makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use.

Smiths Interconnect, a Molex company, reserves the right to modify design and specifications, in order to improve quality, keep pace with technological development or meet specific production requirements.

No reproduction or use without express permission of editorial and pictorial content, in any manner.

Worldwide Support

Connectors

Americas

Sales

connectors.uscsr@smithsinterconnect.com

Technical Support

connectors.ustechsupport@smithsinterconnect.com

Europe

Sales

connectors.emeacsr@smithsinterconnect.com

Technical Support

connectors.emeatechsupport@smithsinterconnect.com

Asia

Sales

asiacsr@smithsinterconnect.com

Technical Support

asiatechsupport@smithsinterconnect.com

Fibre Optics & RF Components

Americas

Sales

focom.uscsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Europe

Sales

focom.emeacsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Asia

Sales

focom.asiacsr@smithsinterconnect.com

Technical Support

focom.techsupport@smithsinterconnect.com

Semiconductor Test

Americas

Sales

semi.uscsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

Europe

Sales

semi.emeacsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

Asia

Sales

semi.asiacsr@smithsinterconnect.com

Technical Support

semi.techsupport@smithsinterconnect.com

Connecting Global Markets

smithsinterconnect.com

