

RESISTOR

CHIP OUTRIGGER 6.0WATTS



DATA SHEET

PART SERIES: CRHA0808XXXXF

SHEET 1 OF 3
Dwg 1016095

EN 20-0100
Revision A

FEATURES


- Wide Band Operation
- High Power
- Coplanar Waveguide Compatible
- Low Capacitance
- Easy Installation
- Wide Resistance Range

APPLICATIONS

- Broadcast
- High Power Filters
- High Power Amplifiers
- Isolators
- Military
- Instrumentation


GENERAL DESCRIPTION

EMC Technology offers the widest selection of chip resistors worldwide. Chip components are offered in both thick and thin film resistive material and available in Alumina, Aluminium Nitride, Beryllium Oxide and CVD Diamond. CRH series feature EMC Technology's patented outrigger resistor technology (US 8, 994, 490) to offer substantially improved power handling over conventional resistors without compromising broadband performance.



ORDERING INFORMATION

Part Identifier: **CRHA0808XXXXF**



SPECIFICATIONS

1.0 ELECTRICAL

Frequency Range:	DC – 25 GHz
Resistance Range:	10 - 500 Ω
Resistance Tolerance:	$\pm 5\%$
Temperature Coefficient of Resistance:	± 200 PPM/ $^{\circ}\text{C}$ Max
Input Power CW:	6.0 Watt
Peak Power:	60W, 10 μs pulse width, 1% duty cycle

2.0 ENVIRONMENTAL

Operating Temperature:	-55 $^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$
Non-operating Temperature:	-65 $^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$

3.0 MARKING

Unit Marking:	Dot Marking, OHMS Value
---------------	-------------------------

4.0 QUALITY ASSURANCE

Visual and Mechanical Inspection:	Per 824W107
DC Resistance Check:	100% DC Resistance Check
Data Retention:	Standard

5.0 PACKAGING

Standard Packaging:	Tape and Reel
---------------------	---------------

RESISTOR

CHIP OUTRIGGER 6.0WATTS



DATA SHEET





PART SERIES: CRHA0808XXXXF

SHEET 2 OF 3
Dwg 1016095

EN 20-0100
Revision A

6.0 MECHANICAL

Substrate Material:	ALN
Resistive Film:	Thick Film
Terminal Material:	Thick Film, Silver/Nickel Plated
Metric Dimensions:	Provided for reference only



Note: Specifications are subject to change.

Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.01 X.XXX = ± 0.002

RESISTOR


CHIP OUTRIGGER 6.0WATTS



DATA SHEET PART SERIES: CRHA0808XXXXF

SHEET 3 OF 3 EN 20-0100
Dwg 1016095 Revision A

7.0 SUGGESTED MOUNTING FOOTPRINT



Part Number	Inches						mm					
	A	B	C	D	E	F	A	B	C	D	E	F
CRHA0808XXX5F	0.045	0.014	0.056	0.018	0.025	0.085	1.143	0.36	1.42	0.44	0.64	2.16