


## ATTENUATOR HIGH RELIABILITY CHIP 200 MILLIWATTS

DATASHEET PART SERIES: HRMXXXXXXX

Sheet 1 of 2  
Doc# HRMXXXXXXX-1009785ECO-084379  
Revision E

## ORDERING INFORMATION

## Part Identifier:

**HRMXX XX XXX**

## SPECIFICATIONS

## 1.0 ELECTRICAL

Nominal Impedance:	50 $\Omega$ .
Frequency Range:	DC – 18 GHz. -.003 dB/dB/°C Thru -.005 dB/dB/°C DC – 18 GHz. -.006 dB/dB/°C Thru -.009 dB/dB/°C DC – 12.4 GHz.
Attenuation Values Available:	0-10 dB in 1 dB increments.
Attenuation Accuracy @ 25°C:	$\pm 0.5$ dB @ 1GHz.
VSWR:	1.30:1 Max @ 1GHz.
Input Power	200 Milliwatts Full Rated Power To 125°C, Derated Linearly to 0 Watts at 150°C.
Temperature Coefficient of	-0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C.
Temperature Coefficient Tolerance:	$\pm 0.001$ dB/dB/°C.

## 2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C.
------------------------	------------------

## 3.0 MARKING

Unit Marking:	dB Value (X), Direction of Shift (N) and TCA Shift (X).
---------------	---

## 4.0 QUALITY ASSURANCE

Verify 100% Visual Pre-Cap Inspection Performed Per TP-8965.

Perform Group A, B and/or C testing as indicated by the part number per TP-8965.

Test Data requirements:

Test data required for customer see TP-8965.

Data retention – 24 months.

Test samples required for customer see TP-8965.

## 5.0 PACKAGING

Standard Packaging:	Serialized Waffle Pack.
---------------------	-------------------------

## 6.0 MECHANICAL



Substrate Material:	Alumina 96%.
Resistive Film:	Thick Film.

## ATTENUATOR HIGH RELIABILITY CHIP 200 MILLIWATTS

DATASHEET PART SERIES: HRMXXXXXXX

Sheet 2 of 2  
Doc# HRMXXXXXXX-1009785ECO-084379  
Revision E

Terminal Material: Thick Film, Nickel Barrier, Solder Plated.  
 Metric Dimensions: Provided for reference only.  
 Workmanship: PER MIL-STD-130.



Unless Otherwise Specified: TOLERANCE: X.XXX = ± 0.005.

## 7.0 FOOTPRINT

Part Number	Inches						mm					
	A	B	C	D	S	W	A	B	C	D	S	W
HRMXXXXXXX	0.022	0.028	0.041	0.013	0.026	0.075	0.56	0.71	1.04	0.33	0.66	1.91

