


## TERMINATION CHIP 150 WATT

DATASHEET PART SERIES: 82A3006F

Sheet 1 of 2  
Doc# 82A3006FECO-083989  
Revision -

## ORDERING INFORMATION

PART IDENTIFIER: 82A3006F

## SPECIFICATIONS

## 1. ELECTRICAL:

Nominal Impedance:	50 $\Omega$ .
Frequency Range:	DC - 1.0 GHz.
VSWR:	DC - 0.5 GHz 1.25:1 Max. 0.5 - 1.0 GHz 1.35:1 Max.
Input Power CW:	150 Watts @ 100°C heat sink, derated linearly to zero power and 150°C.
Peak Power:	1500 Watts (based on 10 $\mu$ s pulse width and 1% duty cycle).
DC Resistance:	50 $\Omega \pm 5\%$ .

## 2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C.
Non-operating Temperature:	-65°C to +150°C.
Temperature Coefficient:	+/-200 PPM / °C max.

## 3. MARKING:

Unit Marking:	No Marking.
---------------	-------------

## 4. QUALITY ASSURANCE:

Visual and Mechanical Inspection:	Per 824W107.
DC Resistance Check:	100% DC Resistance Check.
Data Retention:	Standard.

## 5. PACKAGING:

Standard Packaging:	Tape and Reel.
---------------------	----------------

## TERMINATION CHIP 150 WATT



DATASHEET PART SERIES: 82A3006F

Sheet 2 of 2  
Doc# 82A3006F

ECO-083989  
Revision -

### 6. MECHANICAL:

Substrate Material:	Beryllium Oxide.
Resistive Film:	Thin Film.
Terminal Material:	Silver Plated.
Metric Dimensions:	Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XX =  $\pm 0.02$  X.XXX =  $\pm 0.010$ .