

H-Pin

Stamped contact



The H-Pin is a stamped spring probe with the mechanical, electrical, and thermal performance of a spring probe, and the ease of use and high volume manufacturability of a stamped contact. The H-Pin serves applications without the typical compromises that are generally required when considering cost versus performance.

Excellent mechanical and electrical performance.

Utilizing high volume BeCu stamping technology, combined with a stainless steel spring for mechanical travel, the H-Pin has a working range up to 0.70 mm with a flat spring rate and can be utilized up to 15 GHz with -1.0 dB loss, carry up to 4 A of current and withstand temperatures up to 200 °C.

High volume stamping and quality control.

From pin one to one million, you'll get the same pin every time. Because of our automated H-Pin manufacturing process, you'll be the first person to make contact with your pins.


Robust contact solution for burn-in, programming, and system-level applications.

Benefits

- Compliancy for large package warpage
- Stable contact resistance and force
- Solid beam electrical performance
- Compliancy at high temperatures (180 °C)
- Correlated bi, system evaluation and test
- Reliable power and ground contact
- Stocked inventory and better lead time
- High volume capacity, quality control, and ease of use

Feature Options

- 0.40 mm to 0.70 mm travel
- Flat-spring rate
- BeCu H-Pin
- Stainless steel core spring
- Bandwidth -1 dB @ 15 GHz
- Current carrying capacity
- High-volume stamping
- Reel-to-reel pin insertion



H-Pin detail, showing full deflection (right).

Standard off-the-shelf H-Pins

Version	H027		T033		H033				
LGA									
	L027LL1A		H033LT1A		H033LL2A				
BGA									
	H027WL1A		H033DL2A						
LGA									
	H038LL1A		H057LL1A		H077LL1A				
BGA									
	H038DL1A		H057DL1A		H077DL1A				

Dimensions are in mm.

Technical specifications

	H027	T033	H033	H038	H057	H077
Min Pitch (mm)	0.35	0.40	0.40	0.50	0.70	1.00
Pin Diameter (mm)	0.27	0.33	0.33	0.38	0.57	0.77
Force Options (gF)	8.2	8.6	14.5	30.9	30	34.9
Contact Resistance (mΩ)	<65	<35	<50	<35	<30	<16
Current Rating (A, free air)	0.5	1.8	1.8	2.9	3.0	4.0
Bandwidth at -1dB (GHz)	24.7	50.0	31.7	15.7	18.1	21.9
Self-Inductance (nH)	0.92	0.28	0.75	0.88	0.95	1.04

more > smithsinterconnect.com |   