

ORDERING INFORMATION**PART IDENTIFIER: CT1206****SPECIFICATIONS****1. ELECTRICAL:**

Impedance:	50 Ω Nominal.
Frequency:	DC - 2 GHz.
VSWR:	1.25:1 Max.
Input Power:	Heat Sink 100°C: 10 Watts. (Derate Power Linearly To 0 Watts @ 125°C).

2. ENVIRONMENTAL:

Non-Operating Temperature:	-55°C To +150°C.
Operating Temperature:	-55°C To +125°C.

3. MARKING:

Unit Marking:	No Marking.
---------------	-------------

4. QUALITY ASSURANCE:

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL = 1.0.

Visual And Mechanical Per 824W154.

DC Resistance: 50 Ω \pm 5%.

Data Requirements:

No Test Data Required for Customer.

Data Retention – Standard.



5. PACKAGING:

Standard Bulk Pack per 755W002.

6. MECHANICAL:

Substrate (Material):	Beryllia, ASTM F356.
Terminals and Ground Plane (Material):	Thick Film, Nickel Barrier, Solder Plated.
Resistive Element (Material):	Thick Film.

POWER RATING AND DERATING



Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010.