

ORDERING INFORMATION

PART IDENTIFIER: 82A1058F

SPECIFICATIONS

1. ELECTRICAL:

Nominal Impedance:	50 Ω .
Frequency Range:	DC - 6.0 GHz.
VSWR:	1.11:1 Max.
Input Power CW:	10 Watts @ 100°C heat sink, derated linearly to zero power and 150°C.
Peak Power:	100 Watts (based on 10 μ s pulse width and 1% duty cycle).
DC Resistance:	50 Ω \pm 5 %.

2. ENVIRONMENTAL:

Operating Temperature:	-55°C to +150°C.
Non-operating Temperature:	-65°C to +150°C.
Temperature Coefficient:	+/-200 PPM / °C max.

3. MARKING:

Unit Marking:	No Marking.
---------------	-------------

4. QUALITY ASSURANCE:

Visual and Mechanical Inspection:	Per 824W107.
DC Resistance Check:	100% DC Resistance Check.
Data Retention:	Standard.

5. PACKAGING:

Standard Packaging:	Tape and Reel.
---------------------	----------------

6. MECHANICAL:

Substrate Material:	Beryllium Oxide.
---------------------	------------------



TERMINATION CHIP 10 WATT

DATASHEET PART SERIES: 82A1058F

Sheet 2 of 2
Doc# 82A1058F

ECO-083989
Revision -

Resistive Film: Nichrome.
Terminal Material: Silver.
Metric Dimensions: Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XX = ± 0.02 X.XXX = ± 0.010.