




## ATTENUATOR TEMPERATURE VARIABLE

DATASHEET PART SERIES: TVAXX00XXXF

Sheet 1 of 3  
Doc# TVAXX00XXXF-1010505ECO-084245  
Revision C

## ORDERING INFORMATION

Part Identifier: TVAXX00XXXF



## SPECIFICATIONS

## 1.0 ELECTRICAL

Nominal Impedance:	50 $\Omega$ .
Frequency Range:	DC-6 GHz.
Attenuation Values Available:	1-10 dB in 1 dB increments.
Attenuation Accuracy:	@ 25°C: $\pm 0.5$ dB @ 1 GHz.
VSWR:	1.30:1 Max @ 1 GHz.
Input Power	Negative Shifting: 2 watts cw. Positive Shifting: 0.25 watts cw. Full Rated Power to 125°C, Derated Linearly to 0 watts at 150°C.
Temperature Coefficient of Attenuation:	-0.003, -0.004, -0.005, -0.006, -0.007, and -0.009 dB/dB/°C. 0.003, 0.005, 0.006, 0.007, and 0.008 dB/dB/°C.
Temperature Coefficient Tolerance:	$\pm 0.001$ dB/dB/°C.

## 2.0 ENVIRONMENTAL

Operating Temperature:	-55°C to +150°C.
------------------------	------------------

## 3.0 MARKING

Unit Marking:	dB value (XX), direction of shift (N or P) and TCA shift (X).
---------------	---

## 4.0 QUALITY ASSURANCE

Sample Inspect Per ANSI/ASQC Z1.4 General Inspection, Level II, AQL=1.0.

Visual and Mechanical Examination for Conformance to Outline Drawing Requirements.

Sample Inspection (Destructive Testing).

Select three (3) units from lot and measure DCA every 20°C over the temperature range of -55°C to +125°C; Calculate using linear regression, the slope of the curve.

Calculate TCA using the following formula:

$$TCA = \frac{\text{Slope}}{\text{Attenuation @ 25°C}}$$

Inspection in accordance with 824W107.

Test Data Requirements:

No Data Required for Customer.

Data Retention – 24 Months.



## ATTENUATOR TEMPERATURE VARIABLE

DATASHEETPART SERIES: TVAXX00XXF




Sheet 2 of 3  
Doc# TVAXX00XXF-1010505ECO-084245  
Revision C

## 5.0 PACKAGING

Standard: Standard pack per 755W002.

## 6.0 MECHANICAL

Substrate Material: Alumina, MIL-I-10.  
Terminal Material: Thick Film, lead free plating.  
Workmanship: Per MIL-PRF-55342.  
Resistive Element: Thick Film.  
Metric Dimensions: Provided for reference only.



Unless Otherwise Specified: TOLERANCE: X.XXX = ± 0.005.




## ATTENUATOR TEMPERATURE VARIABLE

DATASHEETPART SERIES: TVAXX00XXXF

Sheet 3 of 3  
Doc# TVAXX00XXXF-1010505ECO-084245  
Revision C

## 7.0 FOOTPRINT

Part Number	Inches						mm					
	A	B	C	D	S	W	A	B	C	D	S	W
TVAXXXXXXXXXXX	0.039	0.060	0.067	0.030	0.032	0.145	0.99	1.52	1.54	0.99	0.99	3.68



## AMERICAS

Sales: [Focom.uscsr@smithsinterconnect.com](mailto:Focom.uscsr@smithsinterconnect.com)Technical Support: [Focom.techsupport@smithsinterconnect.com](mailto:Focom.techsupport@smithsinterconnect.com)

## EUROPE

Sales: [Focom.emeasr@smithsinterconnect.com](mailto:Focom.emeasr@smithsinterconnect.com)Technical Support: [Focom.techsupport@smithsinterconnect.com](mailto:Focom.techsupport@smithsinterconnect.com)

## ASIA

Sales: [Focom.asiacsr@smithsinterconnect.com](mailto:Focom.asiacsr@smithsinterconnect.com)Technical Support: [Focom.techsupport@smithsinterconnect.com](mailto:Focom.techsupport@smithsinterconnect.com)